


INDUSTRIAL COMPONENT DATA

SPT-SMD 1,5/12-H-5,0 R88 1824844 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: SPT-SMD 1,5/12-H-5,0 R88



Manufacturer	PHOENIX CONTACT
MPN / Reference	SPT-SMD 1,5/12-H-5,0 R88
Catalog number	1824844
Category	Printed circuit board terminal
Minimum order	300 Pcs
Document ID	EO-32B80DB445
Generated	2026-09-29

Product Overview

PCB terminal block

Terminal block for printed circuit board, nominal current: 13.5 A, nominal voltage (III/2): 320 V, nominal section: 1.5 mm², number of potentials: 12, number of rows: 1, number of poles per row: 12, article family: SPT 1.5/.. -H-SMD, pitch: 5mm, connection type: Push-in spring connection, mounting: SMD welding, driver/printed circuit board connection direction: 0°, color: black, Pin arrangement: Linear pin arrangement, number of solder pins per potential: 1, packaging type: 88mm wide strap

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1824844

Packing unit 300 pc

Minimum order quantity 300 pc

Catalog page Page 9 (NTK-2014)

GTIN 4046356817042

Weight per Piece (excluding packing) 8.600 g

Custom tariff number 85369010

Country of origin DE (Germany)

Dimensions

Length [l] 13.6 mm

Pitch 5 mm

Dimension a 55 mm

Width [w] 59 mm

Height 7.7 mm

Height [h] 7.7 mm

Pin spacing 7 mm

Hole diameter 1.1 mm

General

Range of articles SPT 1,5/..-H-SMD

Insulating material group IIIa

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 250 V

Rated voltage (III/2) 320 V

Rated voltage (II/2) 500 V

Connection in acc. with standard EN-VDE

Nominal current I_N 13.5 A

Nominal cross section 1.5 mm²

Insulating material LCP

Solder pin surface

Flammability rating according to UL 94 V0

Stripping length 8 mm

Number of positions 12

Connection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 1.5 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 1.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.2 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 1.5 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.2 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 0.75 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 16

Standards and Regulations

Conne...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SPT-SMD 1,5/12-H-5,0 R88 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.