


INDUSTRIAL COMPONENT DATA

FK-MPT 0,5/ 2-3,5-H 1928767 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: FK-MPT 0,5/ 2-3,5-H



Manufacturer	PHOENIX CONTACT
MPN / Reference	FK-MPT 0,5/ 2-3,5-H
Catalog number	1928767
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-A2BFCDAAC7
Generated	2026-09-29

Product Overview

PCB terminal block

Terminal block for printed circuit board, nominal current: 4 A, nominal voltage (III/2): 250 V, nominal section: 0.5 mm², number of potentials: 2, number of rows: 1, number of poles per row: 2, article family: FK-MPT 0.5/.. -H, pitch: 3.5 mm, connection type: Push-in spring connection, mounting: Wave soldering, conductor connection direction/printed circuit board: 0 °, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 4 mm, number of solder pins per potential: 1, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

Key Commercial Data

Orderkey 1928767

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

Catalog page Page 403 (C-1-2013)

GTIN 4017918591212

Weight per Piece (excluding packing) 0.660 g

Custom tariff number 85369010

Country of origin DE (Germany)

Dimensions

Length [l] 9.5 mm

Pitch 3.5 mm

Dimension a 3.5 mm

Width [w] 7.5 mm

Height 8.5 mm

Height [h] 12.5 mm

Solder pin [P] 4 mm

Pin spacing 3.5 mm

Hole diameter 1.2 mm

General

Range of articles FK-MPT 0,5/...-H

Insulating material group IIIa

Rated surge voltage (III/3) 2.5 kV

Rated surge voltage (III/2) 2.5 kV

Rated surge voltage (II/2) 2.5 kV

Rated voltage (III/3) 160 V

Rated voltage (III/2) 250 V

Rated voltage (II/2) 250 V

Connection in acc. with standard EN-VDE

Nominal current I_N 4 ANominal cross section 0.5 mm²Maximum load current 4 A (with 0.5 mm² conductor cross section)

Insulating material PBT

Solder pin surface

Flammability rating according to UL 94 V0

Stripping length 6.5 mm

Number of positions 2

Connection dataConductor cross section solid min. 0.12 mm²Conductor cross section solid max. 0.5 mm²

Conductor cross section AWG min. 26

Conductor cross section AWG max. 20

Standards and Regulations

Connection in acc. with standard EN-VDE

CUL

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.0272607xxeCl@ss 4.127141109eCl@ss 5....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FK-MPT 0,5/ 2-3,5-H with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.