

INDUSTRIAL COMPONENT DATA

MKDSO 2,5/ 2-R 1707195 PHOENIX CONTACT PCB terminal block, Nominal current: 24 A, Nom. voltage: 400 V, Pitch..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKDSO 2,5/ 2-R



Manufacturer	PHOENIX CONTACT
MPN / Reference	MKDSO 2,5/ 2-R
Catalog number	1707195
Category	Printed circuit board terminal
Minimum order	250 Pcs
Document ID	EO-EA23755448
Generated	2026-09-29

Product Overview

PCB terminal block, Nominal current: 24 A, Nom. voltage: 400 V, Pitch: 5 mm, Number of positions: 2, Connection method: Screw connection with tension sleeve, Mounting: Wave soldering, Conductor/PCB connection direction: 0 °, Article with lateral pin exit

Terminal block for printed circuit board, nominal current: 24 A, nominal voltage (III/2): 400 V, nominal section: 2.5 mm², number of potentials: 2, number of rows: 1, number of poles per row: 2, family of articles: MKDSO 2.5/..-R, pitch: 5 mm, connection type: Screw connection with traction capsule, mounting: Wave soldering, conductor connection direction/printed circuit board: 0 °, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5 mm, number of solder pins per potential: 1, packaging type: boxed packaging. Item with right-hand side pin output

Printed circuit board terminal, nominal current: 24 A, rated voltage (III/2): 400 V, nominal cross section: 2.5 mm², number of potentials: 2, number of rows: 1, number of positions per row: 2, product range: MKDSO 2,5/..-R, pitch: 5 mm, connection method: Screw connection with tension sleeve, mounting: Wave soldering, conductor/PCB connection direction: 0 °, color: green, Pin layout: Linear pinning, Solder pin [P]: 3.5 mm, number of solder pins per potential: 1, type of packaging: packed in cardboard. Product with pin output on right side

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Housing (HS)

Additional Product Information

Technical dataProduct propertiesProduct type Printed circuit board terminal

Product family MKDSO 2,5/..-R

Product line COMBICON Terminals M

Type PCB termination block perpendicular to the PCB

Number of positions 2

Pitch 5 mm

Set comprises 2907457 ME 12,5 OT-MKDSO SET

Number of connections 2

Number of rows 1

Number of potentials 2

Pin layout Linear pinning

Solder pins per potential 1

Electrical propertiesNominal current IN 24 A

Nominal voltage UN 400 V

Rated voltage (III/3) 250 V

Rated surge voltage (III/3) 4 kV

Rated voltage (III/2) 400 V

Rated surge voltage (III/2) 4 kV

Rated voltage (II/2) 630 V

Rated surge voltage (II/2) 4 kV

Connection dataConnection technology

Nominal cross section 2.5 mm²

Conductor connection

Connection method Screw connection with tension sleeve

Conductor cross section rigid 0.14 mm² ... 2.5 mm²

Conductor cross section flexible 0.14 mm² ... 2.5 mm²

Conductor cross section AWG 26 ... 14

Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm² ... 2.5 mm²

Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm² ... 2.5 mm²

2 conductors with same cross section, solid 0.14 mm² ... 0.75 mm²

2 conductors with same cross section, flexible 0.14 mm² ... 0.75 mm²

2 conductors with same cross section, flexible, with ferrule without plastic sleeve 0.25 mm² ... 0.75 mm²

2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve 0.5 mm² ... 1.5 mm²

Stripping length 8 mm

Tightening torque 0.5....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKDSO 2,5/ 2-R with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.