INDUSTRIAL COMPONENT DATA

MKKDS 3/ 3-5,08 1721731 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKKDS 3/ 3-5,08



Manufacturer	PHOENIX CONTACT
MPN / Reference	MKKDS 3/ 3-5,08
Catalog number	1721731
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-1C4251AD6F
Generated	2026-11-18

Product Overview

PCB terminal block
Terminal block for printed circuit board, rated current: 22 A, rated voltage (III/2): 400 V, rated cross-section: 2.5 mm², number of potentials: 6, number of rows: 2, number of poles per row: 3, article family: MKKDS 3, pitch: 5.08 mm, connection type: Screw connection with traction capsule, screw clamping method: L Longitudinal slot, mounting: Wave soldering, conductor/printed circuit board connection direction: 0 °, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 5 mm, number of soldering pins per potential: 1, packaging type: boxed packaging. The item can be aligned with different numbers of poles!

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1721731
Packing unit 50 pc
Catalog page Page 109 (C-1-2013)
GTIN 4017918025113
Weight per Piece (excluding packing) 14.240 g
Custom tariff number 85369010
Country of origin DE (Germany)
Dimensions

Length [l] 22.3 mm
Pitch 5.08 mm
Dimension a 10.16 mm
Width [w] 17.78 mm
Height 31.5 mm
Height [h] 36.5 mm
Solder pin [P] 5 mm
Hole diameter 1.3 mm
General
Range of articles MKKDS 3
Insulating material group I
Rated surge voltage (III/3) 4 kV
Rated surge voltage (III/2) 4 kV
Rated surge voltage (II/2) 4 kV
Rated voltage (III/3) 250 V
Rated voltage (III/2) 400 V
Rated voltage (II/2) 630 V
Connection in acc. with standard EN-VDE
Nominal current IN 22 A
Nominal cross section 2.5 mm²
Maximum load current 24 A (with 4 mm² conductor cross section)
Insulating material PA
Contact material Sn
Solder pin surface
Flammability rating according to UL 94 V0
Internal cylindrical gage A3
Stripping length 7 mm
Number of positions 3
Screw thread M3
Tightening torque, min 0.5 Nm
Tightening torque max 0.6 Nm
Connection data
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 4 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 2.5 mm²
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 1.5 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²
Conductor cross section fle...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKKDS 3/ 3-5,08 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.