

INDUSTRIAL COMPONENT DATA

SMKDS 2,5/10-5,08 1736780 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: SMKDS 2,5/10-5,08



Manufacturer	PHOENIX CONTACT
MPN / Reference	SMKDS 2,5/10-5,08
Catalog number	1736780
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-08F419B71A
Generated	2026-09-28

Product Overview

PCB terminal block

Terminal block for printed circuit board, nominal current: 20 A, nominal voltage (III/2): 400 V, nominal cross-section: 2.5 mm², number of potentials: 10, number of rows: 1, number of poles per row: 10, article family: SMKDS 2.5, pitch: 5.08 mm, connection type: Screw connection with traction capsule, screw clamping method: L Longitudinal slot, mounting: Wave soldering, conductor/printed circuit board connection direction: 50 °, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5 mm, number of solder pins per potential: 1, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1736780

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 103 (C-1-2013)

GTIN 4046356181983

Weight per Piece (excluding packing) 23.740 g

Custom tariff number 85369010

Country of origin PL (Poland)

Dimensions

Length [l] 14.25 mm

Pitch 5.08 mm

Dimension a 45.72 mm

Width [w] 50.8 mm

Height 19.4 mm

Height [h] 22.9 mm

Solder pin [P] 3.5 mm

Hole diameter 1.4 mm

General

Range of articles SMKDS 2,5

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 250 V

Rated voltage (III/2) 400 V

Rated voltage (II/2) 630 V

Connection in acc. with standard EN-VDE

Nominal current IN 20 A

Nominal cross section 2.5 mm²

Solder pin surface

Internal cylindrical gage A3

Stripping length 11 mm

Number of positions 10

Screw thread M3

Tightening torque, min 0.5 Nm

Tightening torque max 0.6 Nm

Connection data

Conductor cross section AWG min. 26

Conductor cross section AWG max. 14

2 conductors with same cross section, solid min. 0.14 mm²

2 conductors with same cross section, solid max. 0.75 mm²

2 conductors with same cross section, stranded min. 0.14 mm²

2 conductors with same cross section, stranded max. 0.75 mm²

2 conductors with same cross section, stranded, ferrules without plastic sleeve, min. 0.25 mm²

2 conductors with same cross section, stranded, ferrules without plastic sleeve, max. 0.75 mm²

2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min. 0.5 m...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SMKDS 2,5/10-5,08 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.