

INDUSTRIAL COMPONENT DATA

SPT 2,5/11-H-5,0 1991066 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: SPT 2,5/11-H-5,0



Manufacturer	PHOENIX CONTACT
MPN / Reference	SPT 2,5/11-H-5,0
Catalog number	1991066
Category	Printed circuit board terminal
Minimum order	40 Pcs
Document ID	EO-027DFB9536
Generated	2026-09-29

Product Overview

PCB terminal block

Terminal block for printed circuit board, nominal current: 24 A, nominal voltage (III/2): 400 V, nominal section: 2.5 mm², number of potentials: 11, number of rows: 1, number of poles per row: 11, family of articles: SPT 2.5/.. -H, pitch: 5mm, connection type: Push-in spring connection, mounting: Wave soldering, conductor/printed circuit board connection direction: 0°, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 2.5mm, number of solder pins per potential: 2, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1991066

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

Catalog page Page 143 (C-1-2013)

GTIN 4046356104692

Weight per Piece (excluding packing) 12.590 g

Custom tariff number 85369010

Country of origin DE (Germany)

Dimensions

Length [l] 14.4 mm

Pitch 5 mm

Dimension a 50 mm

Width [w] 56.4 mm

Height 13.5 mm

Height [h] 16 mm

Solder pin [P] 2.5 mm

Pin spacing 5 mm

Hole diameter 1.1 mm

General

Range of articles SPT 2,5/...-H

Insulating material group I

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 250 V

Rated voltage (III/2) 400 V

Rated voltage (II/2) 630 V

Connection in acc. with standard EN-VDE

Nominal current I_N 24 ANominal cross section 2.5 mm²

Maximum load current 24 A

Insulating material PA

Solder pin surface

Flammability rating according to UL 94 V0

Internal cylindrical gage A3

Stripping length 10 mm

Number of positions 11

Connection dataConductor cross section solid min. 0.2 mm²Conductor cross section solid max. 4 mm²Conductor cross section flexible min. 0.2 mm²Conductor cross section flexible max. 2.5 mm²Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm² Stripping length 8 mmConductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm² Stripping length 8 mmConductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm² Stripping length 8 mm

Conductor c...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SPT 2,5/11-H-5,0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.