


INDUSTRIAL COMPONENT DATA

ZFKDSA 1,5C-6,0-EX 1732124 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: ZFKDSA 1,5C-6,0-EX



Manufacturer	PHOENIX CONTACT
MPN / Reference	ZFKDSA 1,5C-6,0-EX
Catalog number	1732124
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-2FC2FFDE8E
Generated	2026-09-29

Product Overview

PCB terminal block

Printed circuit board terminal, rated current: 16 A, rated section: 1.5 mm², Number of potentials: 1, Number of rows: 1, Number of poles per row: 1, item family: ZFKDS(A) 1.5C-EX, pitch: 5 mm, connection type: Spring connection, mounting: Wave welding, connection direction conductor/printed circuit board: 45 °, color: green, Pin layout: Linear pin arrangement, Pin length [P]: 3.5 mm, packaging type: boxed packaging. Terminal terminal terminal for termination of individually composed blocks.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1732124

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 161 (C-1-2013)

GTIN 4046356280716

Weight per Piece (excluding packing) 1.190 g

Custom tariff number 85369010

Country of origin PL (Poland)

Dimensions

Length [l] 14.1 mm

Pitch 5 mm

Width [w] 5 mm

Height 12.75 mm

Height [h] 16.25 mm

Solder pin [P] 3.5 mm

Pin spacing 5.08 mm

Hole diameter 1.1 mm

General

Range of articles ZFKDS(A) 1,5C-EX

Insulating material group I

Nominal cross section 1.5 mm²

Insulating material PA

Solder pin surface

Flammability rating according to UL 94 V0

Number of positions 1

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.0271411111eCl@ss 4.127141109eCl@ss 5.027141190eCl@ss 5.127261100eCl@ss 6.027261100eCl@ss
7.027440401eCl@ss 8.027440401eCl@ss 9.027440401

ETIM 3.0EC001121ETIM 4.0EC002643ETIM 5.0EC002643ETIM 6.0EC002643

UNSPSC 6.0130211801UNSPSC 7.090139121432UNSPSC 1139121432UNSPSC 12.0139121432UNSPSC
13.239121432

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ZFKDSA 1,5C-6,0-EX with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.