
INDUSTRIAL COMPONENT DATA

PCV 6-16/ 8-G-10,16 1922543 PHOENIX CONTACT Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: PCV 6-16/ 8-G-10,16



Manufacturer	PHOENIX CONTACT
MPN / Reference	PCV 6-16/ 8-G-10,16
Catalog number	1922543
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-25E23CC149
Generated	2026-11-19

Product Overview

Feed-through header
Printed circuit board base housing, nominal section: 6 mm², color: green, nominal current: 76 A (41 A in combination with PC 6 connector), nominal voltage (III/2): 1000 V, contact surface: silver, contact type: Male, number of potentials: 8, number of rows: 1, number of poles: 8, number of connections: 8, family of articles: PCV 6-16/.. -G, pitch: 10.16 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 4 mm, number of soldering pins per potential: 3, plug-in system: COMBICON PC 16, Plug-in face orientation: Standard, locking: without, fixing type: without, packaging type: box-packed, The 76 A rated current is valid in combination with PC 16 family connectors. In combination with PC 6 connectors, 41 A (50 A according to UL) is achieved.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1922543
Packing unit 50 pc
Note Made to Order (non-returnable)
Catalog page Page 195 (CC-2002)
GTIN 4017918727093
Weight per Piece (excluding packing) 27.930 g
Custom tariff number 85366930

Country of origin PL (Poland)
Dimensions
Pitch 10.16 mm
Dimension a 71.12 mm
Height 29 mm
Length of the solder pin 4 mm
Pin dimensions 0.8 x 1.2 mm
General
Range of articles PCV 6-16/..-G
Rated voltage (III/3) 630 V
Connection in acc. with standard EN-VDE
Nominal current IN 76 A
Color green
Number of positions 8
Standards and Regulations
Connection in acc. with standard EN-VDE
CUL
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440402eCl@ss 8.027440402eCl@ss 9.027440402
ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637
UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC 13.239121409

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PCV 6-16/ 8-G-10,16 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.