
INDUSTRIAL COMPONENT DATA

SAC-3P-M12MS/ 3,0-PUR BK 1409296 PHOENIX CONTACT Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-M12MS/ 3,0-PUR BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-M12MS/ 3,0-PUR BK
Catalog number	1409296
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-D852279EDE
Generated	2026-11-18

Product Overview

Sensor/actuator cable

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1409296
Packing unit 1 pc
Minimum order quantity 50 pc
Note Made to Order (non-returnable)
GTIN 4046356867849
Weight per Piece (excluding packing) 82.000 g
Custom tariff number 85444290
Country of origin DE (Germany)
Dimensions
Length of cable 3 m
Stripping length of the free conductor end 50 mm
Ambient conditions
Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)
Degree of protection IP65

IP67
General
Rated current at 40°C 4 A
Rated voltage 250 V AC
250 V DC
Insulation resistance >= 100 M?
Coding A - standard
Overvoltage category II
Degree of pollution 3
Insertion/withdrawal cycles >= 100
Torque 0.4 Nm
Material
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Cable
Cable type PUR halogen-free black
Cable type (abbreviation) PUR
Cable abbreviation Li9Y11Y
UL AWM style 20549
Conductor cross section 3x 0.34 mm² (Signal line)
AWG signal line 22
Conductor structure signal line 42x 0.10 mm
Core diameter including insulation 1.27 mm ±0.02 mm (Signal line)
Thickness, insulation >= 0.21 mm (Core insulation)
approx. 0.5 mm (Outer cable sheath)
Wire colors brown, blue, black
Overall twist 3 wires, twisted
External sheath, color black-gray RAL 7021
External cable diameter D 3.85 mm ±0.15 mm
Smallest bending radius, fixed installation 19 mm
Smallest bending radius, movable installation 38 mm
Number of....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-M12MS/ 3,0-PUR BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.