INDUSTRIAL COMPONENT DATA

C-PCI 6/2,7 3240068 PHOENIX CONTACT Cable lug

Brand: PHOENIX CONTACT | Manufacturer Part Number: C-PCI 6/2,7



Manufacturer	PHOENIX CONTACT
MPN / Reference	C-PCI 6/2,7
Catalog number	3240068
Category	Solderless copper terminals for copper conductors
Minimum order	50 Pcs
Document ID	EO-EAF9DD8FAE
Generated	2026-11-18

Product Overview

Cable lug
Male cable lug, yellow, 4 - 6 mm², L1=12 mm
Pin cable lug, yellow, 4 - 6 mm2, L1=12 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > TOOL fox

Additional Product Information

Technical dataProduct propertiesProduct type Connector
Data management status
Article revision 00
Electrical propertiesFuse yes
DimensionsDimensional drawing
Sleeve length 27.5 mm
Length of the insulating material sleeve 14 mm
Length contact range 13.5 mm
Maximum stripping length 9 mm
Min. material thickness 0.8 mm
Inner dimensions of the insulating collar 6.6 mm
Internal dimensions
Internal diameter 2.7 mm
Material specificationsColor yellow (RAL 1018)

Material Copper
Flammability rating according to UL 94 V2
Coating tin-plated
Insulating material PA
Components halogen-free
Mechanical propertiesTechnical data
Sleeve length 27.5 mm
Environmental and real-life conditionsAmbient conditions
Ambient temperature (operation) -20 °C ... 105 °C

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / C-PCI 6/2,7 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.