INDUSTRIAL COMPONENT DATA

PML-T110 (26X280)R 1014247 PHOENIX CONTACT Pipeline markers

Brand: PHOENIX CONTACT | Manufacturer Part Number: PML-T110 (26X280)R



Manufacturer	PHOENIX CONTACT
MPN / Reference	PML-T110 (26X280)R
Catalog number	1014247
Category	Warning/signing plate
Minimum order	1 Pcs
Document ID	EO-6906101F3B
Generated	2026-11-19

Product Overview

Pipeline markers
Pipe marker, Roll, blue, preprinted, labelable with: THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, THERMOMARK ROLL X1, THERMOMARK ROLL 2.0, THERMOMARK ROLL, mounting class: glued, diameter: 0 mm, useful surface: 26 x 280 mm, Number of individual indexes: 250

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material

Additional Product Information

Key Commercial Data
Orderkey 1014247
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 383 (C-3-2017)
GTIN 4046356784436
Weight per Piece (excluding packing) 587.100 g
Custom tariff number 39199080
Country of origin DE (Germany)
Dimensions
Length (b) 26 mm
Width (a) 280 mm

Height (c) 26 mm
Diameter 0.00 mm
Ambient conditions
Ambient temperature (operation) -40 °C ... 150 °C
Recommended storage conditions 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.
General
Color blue
Type Rectangle
Components Silicone-free
Material Polyester
RoHS compliant Yes
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Number of individual labels 250
Adhesive Acrylic
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Procedure
Test duration 96 h
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Procedure A
Test duration 96 h
Salt spray testing result Test passed
Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07
Result Test passed
Foil strength 50 µm
Adhesive strength 46 µm
Marking mounting type adhesive
Standards and Regulations
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Classifications
eCl@ss 10.0.140200202eCl@ss 4.027141199eCl@ss 4.127141199eCl@ss 5.027371301eCl@ss 5.127371300eCl@ss 6.027149100eCl@ss 7.027149129eCl@ss....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PML-T110 (26X280)R with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.