INDUSTRIAL COMPONENT DATA

PC 4/ 3-G-7,62 CRWH 1973398 PHOENIX CONTACT Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: PC 4/ 3-G-7,62 CRWH



Manufacturer	PHOENIX CONTACT
MPN / Reference	PC 4/ 3-G-7,62 CRWH
Catalog number	1973398
Category	Printed circuit board connector
Minimum order	2000 Pcs
Document ID	EO-C841FB3A36
Generated	2026-11-19

Product Overview

Feed-through header
Printed circuit board base case, nominal section: 4 mm², color: cream white, nominal current: 20 A, nominal voltage (III/2): 630 V, contact surface: Tin, type of contact: Male, number of potentials: 3, number of rows: 1, number of poles: 3, number of connections: 3, family of articles: PC 4/.. -G, pitch: 7.62 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 5 mm, number of solder pins per potential: 2, plug-in system: COMBICON PC 4, Plug-in face orientation: Standard, lock: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1973398
Packing unit 50 pc
Minimum order quantity 50 pc
Note Made to Order (non-returnable)
GTIN 4017918961619
Weight per Piece (excluding packing) 4.960 g
Custom tariff number 85366990
Country of origin DE (Germany)
Dimensions

Length [l] 29 mm
Width 22.84 mm
Pitch 7.62 mm
Dimension a 15.24 mm
Width [w] 22.84 mm
Height [h] 19.25 mm
Height 14.25 mm
Length of the solder pin 5 mm
Pin dimensions 1 x 0.8 mm
Length 29 mm
General
Range of articles PC 4/..-G
Rated voltage (III/3) 400 V
Connection in acc. with standard EN-VDE
Nominal current IN 20 A
Color cream
Number of positions 3
Standards and Regulations
Connection in acc. with standard EN-VDE
CSA
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440402eCl@ss 8.027440402eCl@ss 9.027440402
ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637
UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC 13.239121409

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PC 4/ 3-G-7,62 CRWH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.