
INDUSTRIAL COMPONENT DATA

# EMLP 24 (30X12) BK CUS 0824365 PHOENIX CONTACT Plastic label with drill hole

**Brand: PHOENIX CONTACT | Manufacturer Part Number: EMLP 24 (30X12) BK CUS**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | EMLP 24 (30X12) BK CUS |
| Catalog number | 0824365 |
| Category | Labelling for terminal block |
| Minimum order | 1 Pcs |
| Document ID | EO-0E6E83102D |
| Generated | 2026-11-18 |

## Product Overview

Plastic label with drill hole
Plastic sign with hole, available: per card, black, labeled according to customer's instructions, mounting class: glued, usable surface: 30 x 12 mm, Number of individual indexes: 8

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > CABINET add-on |

## Additional Product Information

Key Commercial Data
Orderkey 0824365
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 295 (C-5-2013)
GTIN 4046356352413
Weight per Piece (excluding packing) 21.690 g
Custom tariff number 49119900
Country of origin DE (Germany)
Dimensions
Length (b) 40 mm
Width (a) 30 mm
Ambient conditions

Ambient temperature (operation) -40 °C ... 80 °C
Recommended storage conditions 20°C/50% relative humidity. Storage in the original packaging is recommended.
General
Color black
Components free from silicone and halogen
Material TRANSPLY-ABS
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Number of individual labels 8
Number of individual labels per row 2
Adhesive Acrylic
Printability Plotter
Engraving
Device 5144615 CMS-P1-PLOTTER
5145546 P1 ENGRAVING UNIT
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Test duration 96 h
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Test duration 96 h
Salt spray testing result Test passed
Alternating condensation climate with SO2 test specification DIN 50018:2013-05
Climate level AHT 1.0 S
Cycles 2
Condensation test result Test passed
Adhesive strength 50 µm
Marking mounting type adhesive
Standards and Regulations
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Classifications
eCl@ss 10.0.127400629eCl@ss 4.024190219eCl@ss 4.124190219eCl@ss 5.027149103eCl@ss 5.1271...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EMLP 24 (30X12) BK CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.