
INDUSTRIAL COMPONENT DATA

PLC-BPT- 24UC/21-21/H 1012005 PHOENIX CONTACT Relay base

Brand: PHOENIX CONTACT | Manufacturer Part Number: PLC-BPT- 24UC/21-21/H



Manufacturer	PHOENIX CONTACT
MPN / Reference	PLC-BPT- 24UC/21-21/H
Catalog number	1012005
Category	Relay socket
Minimum order	10 Pcs
Document ID	EO-69AF4BE153
Generated	2026-11-18

Product Overview

Relay base
14 mm PLC base terminal without relay equipment, for mounting on NS 35/7.5 rail, Push-in connection, 2 switched contacts, Input voltage 24 V AC/DC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data
Orderkey 1012005
Packing unit 10 pc
Minimum order quantity 10 pc
Note Made to Order (non-returnable)
GTIN 4055626487335
Weight per Piece (excluding packing) 51.740 g
Custom tariff number 85366990
Country of origin DE (Germany)
Dimensions
Width 14 mm
Height 80 mm
Depth 104 mm

Ambient conditions
Ambient temperature (operation) -40 °C ... 60 °C
Ambient temperature (storage/transport) -40 °C ... 85 °C
Input data
Nominal input voltage UN 24 V AC/DC
Status display LED
Protective circuit Bridge rectifier
Connection data, input side
Connection name Input side
Connection method Push-in connection
Stripping length 10 mm
Conductor cross section solid 0.14 mm² ... 2.5 mm²
Conductor cross section flexible 0.14 mm² ... 2.5 mm²
0.2 mm² ... 2.5 mm² ()
2x 0.5 mm² ... 1 mm² ()
Conductor cross section AWG 26 ... 14
Connection data, output side
Connection name Output side
Connection method Push-in connection
Stripping length 10 mm
Conductor cross section solid 0.14 mm² ... 2.5 mm²
Conductor cross section flexible 0.14 mm² ... 2.5 mm²
0.2 mm² ... 2.5 mm² ()
2x 0.5 mm² ... 1 mm² ()
Conductor cross section AWG 26 ... 14
General
Color green
Operating mode 100% operating factor
Mounting position any
Assembly instructions In rows with zero spacing
Standards and Regulations
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PLC-BPT- 24UC/21-21/H with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.