INDUSTRIAL COMPONENT DATA

PLC-BSC- 12DC/ 1IC/ACT 1090867 PHOENIX CONTACT 14 mm PLC basic terminal block for high switch-on currents wi..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PLC-BSC- 12DC/ 1IC/ACT



Manufacturer	PHOENIX CONTACT
MPN / Reference	PLC-BSC- 12DC/ 1IC/ACT
Catalog number	1090867
Category	Relay socket
Minimum order	10 Pcs
Document ID	EO-B0818D8ECB
Generated	2026-11-18

Product Overview

14 mm PLC basic terminal block for high switch-on currents with screw connection, without relay or solid-state relay, for mounting on DIN rail NS 35/7,5, with load return line connection (BB), 1 N/O contact, input voltage 12 V DC
14 mm PLC base terminal block for high clamping currents with screw connection, without relay or solid-state relay equipment, for mounting on NS 35/7.5 rail, with load return line (BB) connection, 1 closing contact, input voltage 12 V AC/DC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data
Orderkey 1090867
Packing unit 1 pc
GTIN 4055626901381
Weight per Piece (excluding packing) 0.000 g
Custom tariff number 85366990
Country of origin DE (Germany)
Drawings
Dimensions
Input data
General

Connection data 2
Environmental Product Compliance
Note
Ambient conditions
Output data
Connection data
Standards and Regulations
Classifications
Drawings
Circuit diagram
Back to topNote
Note Separating plate PLC-ATP must be installed for voltages larger than 250 V (L1, L2, L3) between identical terminal blocks in adjacent modules.
The PLC-ATP separating plate should be installed for safe isolation between adjacent modules
The PLC-ATP separating plate is required at the start and end of every PLC terminal strip.
The system installer must ensure the touch protection of the product (at voltages > 25 V AC/60 V DC). The product is a built-in device without protection against direct contact.
Back to topDimensions
Width 14 mm
Height 80 mm
Depth 94 mm
Back to topAmbient conditions
Ambient temperature (operation) -40 °C ... 60 °C
Ambient temperature (storage/transport) -40 °C ... 85 °C
Maximum altitude <= 2000 m
Degree of protection IP20
>= IP54 (Installation location)
Back to topInput data
Nominal input voltage UN 12 V DC
Protective circuit Damping diode
Polarity protection diode
Back to topOutput data
Compatible components Miniature relay, 2904475 REL-MR- 12DC/1IC, 1081616 REL-MR- 12DC/1ICT
Back to topGeneral
Color gray
Operating mode 100% operating factor
Mounting pos...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PLC-BSC- 12DC/ 1IC/ACT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.