INDUSTRIAL COMPONENT DATA

PLC-BSC- 24DC/21/SO46 2980458 PHOENIX CONTACT Relay base

Brand: PHOENIX CONTACT | Manufacturer Part Number: PLC-BSC-24DC/21/SO46



Manufacturer	PHOENIX CONTACT
MPN / Reference	PLC-BSC-24DC/21/SO46
Catalog number	2980458
Category	Relay socket
Minimum order	10 Pcs
Document ID	EO-8A205FA982
Generated	2026-11-18

Product Overview

Relay base
6.2 mm PLC base terminal block against eddy current and/or eddy voltages on the control side with screw connection, without relay or solid-state relay equipment, for mounting on NS 35/7.5 rail, with extended input current absorption, 1 switched contact, input voltage 24 V DC
6.2 mm PLC base terminal, against interference currents and/or voltages on the control side with screw connection, without equipment. relay or solid-state relay, for mounting on NS 35/7.5 mounting rail, with increased input power consumption, 1 changeover contact, tens. of ingr. 24 V DC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Relays

Additional Product Information

Key Commercial Data
Orderkey 2980458
Packing unit 10 pc
Minimum order quantity 10 pc
GTIN 4017918930219
Weight per Piece (excluding packing) 28.520 g
Custom tariff number 85366990
Country of origin DE (Germany)
Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area
Dimensions
Width 6.2 mm
Height 80 mm
Depth 94 mm
Ambient conditions
Ambient temperature (operation) -40 °C ... 55 °C
Ambient temperature (storage/transport) -40 °C ... 85 °C
Input data
Nominal input voltage UN 24 V DC
Status display LED
Protective circuit Free-wheeling diode, polarity protection diode, resistor
Damping diode
Connection data, input side
Connection name Input side
Connection method Screw connection
Stripping length 8 mm
Screw thread M3
Conductor cross section solid 0.14 mm² ... 2.5 mm²
Conductor cross section flexible 0.14 mm² ... 2.5 mm²
0.2 mm² ... 2.5 mm² ()
2x 0.5 mm² ... 1.5 mm² ()
Conductor cross section AWG 26 ... 14
Connection data, output side
Connection name Output side
Connection method Screw connection
Stripping length 8 mm
Screw thread M3
Conductor cross section solid 0.14 mm² ... 2.5 mm²
Conductor cross section flexible 0.14 mm² ... 2.5 mm²
0.2 mm² ... 2.5 mm² ()
2x 0.5 mm² ... 1.5 mm² ()
Conductor cross section AWG 26 ... 14
General
Protective circuit Free-wheeling diode, polarity protection diode, resistor
Color green
Operating mode 100% operating factor
Mounting position any
Assembly instructions In rows with zero spacing
Standards and...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PLC-BSC-24DC/21/SO46 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.