INDUSTRIAL COMPONENT DATA

PLC-OPT- 60DC/300DC/1 2900384 PHOENIX CONTACT PLC-INTERFACE, integrated solid-state relay, with Push-in conn..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PLC-OPT-60DC/300DC/1



Manufacturer	PHOENIX CONTACT
MPN / Reference	PLC-OPT-60DC/300DC/1
Catalog number	2900384
Category	Optocoupler
Minimum order	1 Pcs
Document ID	EO-D63C22E75D
Generated	2026-11-18

Product Overview

PLC-INTERFACE, integrated solid-state relay, with Push-in connection, for mounting on NS 35/7,5 DIN rails, input: 60 V DC, output: 12 - 300 V DC/1 A
PLC INTERFACE, integrated solid-state relay, with push-in connection, for symmetrical rail mounting NS 35/7.5, input: 60 V DC, output: 12-300 V DC/1 A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Relays

Additional Product Information

Note
Utilization restriction EMC: class A product, see manufacturer's declaration in the download area
Dimensions
Width 6.2 mm
Height 80 mm
Depth 86 mm
Ambient conditions
Ambient temperature (operation) -25 °C ... 60 °C
Ambient temperature (storage/transport) -40 °C ... 85 °C
Input data

Nominal input voltage UN 60 V DC
Input voltage range in reference to UN 0.8 ... 1.2
Input voltage range 48 V DC ... 60 V DC
Switching threshold "0" signal in reference to UN <= 0.4
Switching threshold "1" signal in reference to UN >= 0.8
Typical input current at UN 5 mA
Typical response time 0.3 ms
Typical turn-off time 0.7 ms
Operating voltage display Yellow LED
Type of protection Reverse polarity protection
Surge protection
Protective circuit/component Polarity protection diode
Varistor
Transmission frequency 50 Hz
Output data
Designation Output data
Output voltage range 12 V DC ... 300 V DC (Partition plate PLC-ATP must be installed for voltages larger than 250 V (L1, L2, L3) between identical terminal points in adjacent modules. Potential bridging is then carried out with FBST 8-PLC... or ...FBST 500...)
Limiting continuous current 1 A (see derating curve)
Voltage drop at max. limiting continuous current < 500 mV
Type of protection Reverse polarity protection
Surge protection
Protective circuit/component Polarity protection diode
Varistor
Connection data, input side
Connection name Input side
Connection method Push-in connection
Stripping length 8 mm
Conductor cross section solid 0.14 mm² ....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PLC-OPT-60DC/300DC/1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.