INDUSTRIAL COMPONENT DATA

# PLC-RPT-230UC/21 2900305 PHOENIX CONTACT Relay Module

**Brand: PHOENIX CONTACT | Manufacturer Part Number: PLC-RPT-230UC/21**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | PLC-RPT-230UC/21 |
| Catalog number | 2900305 |
| Category | Switching relay |
| Minimum order | 1 Pcs |
| Document ID | EO-DD73F73ED9 |
| Generated | 2026-11-18 |

## Product Overview

Relay Module
PLC-INTERFACE, consists of a PLC-BPT.../21 base terminal block with Push-in connection and plug-in miniature relay with power contact, for mounting on NS 35/7.5 symmetrical rail, 1 reverse contact, input voltage 230 V AC/220 V DC

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Industrial Relays |

## Additional Product Information

Key Commercial Data
Orderkey 2900305
Packing unit 10 pc
Catalog page Page 372 (C-5-2017)
GTIN 4046356507004
Weight per Piece (excluding packing) 31.270 g
Custom tariff number 85364900
Country of origin DE (Germany)
Note
Utilization restriction EMC: class A product, see manufacturer's declaration in the download area
Note Separating plate PLC-ATP must be installed for voltages larger than 250 V (L1, L2, L3) between identical terminal blocks in adjacent modules. Potential bridging is then carried out with FBST 8-PLC... or FBST 500....
Dimensions

Width 6.2 mm
Height 80 mm
Depth 94 mm
Ambient conditions
Ambient temperature (operation) -40 °C ... 55 °C
Ambient temperature (storage/transport) -40 °C ... 85 °C
Coil side
Nominal input voltage UN 230 V AC
220 V DC
Typical input current at UN 3.2 mA (at UN= 230 V AC)
3 mA (at UN= 220 V DC)
Typical response time 7 ms
Typical release time 15 ms
Protective circuit Bridge rectifier Bridge rectifier
Operating voltage display Yellow LED
Power dissipation for nominal condition 0.74 W
Contact side
Contact type 1 PDT
Type of switch contact Single contact
Contact material AgSnO
Maximum switching voltage 250 V AC/DC (The separating plate PLC-ATP should be installed for voltages larger than 250 V (L1, L2, L3) between identical terminal blocks in adjacent modules. Potential bridging is then carried out with FBST 8-PLC... or ...FBST 500...)
Minimum switching voltage 5 V (at 100 mA)
Min. switching current 10 mA (at 12 V)
Maximum inrush current 10 A....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PLC-RPT-230UC/21 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.



Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.