INDUSTRIAL COMPONENT DATA

PLC-RPT- 24UC/21 2900300 PHOENIX CONTACT Relay Module

Brand: PHOENIX CONTACT | Manufacturer Part Number: PLC-RPT-24UC/21



Manufacturer	PHOENIX CONTACT
MPN / Reference	PLC-RPT-24UC/21
Catalog number	2900300
Category	Switching relay
Minimum order	1 Pcs
Document ID	EO-AE9A18144B
Generated	2026-11-18

Product Overview

Relay Module
PLC-INTERFACE, consists of a PLC-BPT.../21 base terminal block with Push-in connection and plug-in miniature relay with power contact, for mounting on NS 35/7.5 symmetrical rail, 1 reverse contact, input voltage 24VDC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Relays

Additional Product Information

Key Commercial Data
Orderkey 2900300
Packing unit 10 pc
Catalog page Page 372 (C-5-2017)
GTIN 4046356509008
Weight per Piece (excluding packing) 31.270 g
Custom tariff number 85364190
Country of origin DE (Germany)
Note
Utilization restriction EMC: class A product, see manufacturer's declaration in the download area
Note Separating plate PLC-ATP must be installed for voltages larger than 250 V (L1, L2, L3) between identical terminal blocks in adjacent modules. Potential bridging is then carried out with FBST 8-PLC... or FBST 500....
Dimensions

Width 6.2 mm
Height 80 mm
Depth 94 mm
Ambient conditions
Ambient temperature (operation) -40 °C ... 60 °C
Ambient temperature (storage/transport) -40 °C ... 85 °C
Coil side
Nominal input voltage UN 24 V AC/DC
Typical input current at UN 11 mA (at UN= 24 V AC)
8.5 mA (at UN= 24 V DC)
Typical response time 6 ms
Typical release time 15 ms
Protective circuit Bridge rectifier Bridge rectifier
Operating voltage display Yellow LED
Power dissipation for nominal condition 0.26 W
Contact side
Contact type 1 PDT
Type of switch contact Single contact
Contact material AgSnO
Maximum switching voltage 250 V AC/DC (The separating plate PLC-ATP should be installed for voltages larger than 250 V (L1, L2, L3) between identical terminal blocks in adjacent modules. Potential bridging is then carried out with FBST 8-PLC... or ...FBST 500...)
Minimum switching voltage 5 V (at 100 mA)
Min. switching current 10 mA (at 12 V)
Maximum inrush current 10 A (4 s)
Li...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PLC-RPT-24UC/21 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.