INDUSTRIAL COMPONENT DATA

PLC-RPT- 48DC/21-21AU 2900340 PHOENIX CONTACT PLC-INTERFACE, consisting of PLC-BPT.../21-21 basic terminal b..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PLC-RPT-48DC/21-21AU



Manufacturer	PHOENIX CONTACT
MPN / Reference	PLC-RPT-48DC/21-21AU
Catalog number	2900340
Category	Switching relay
Minimum order	10 Pcs
Document ID	EO-7968516729
Generated	2026-11-18

Product Overview

PLC-INTERFACE, consisting of PLC-BPT.../21-21 basic terminal block with push-in connection and plug-in miniature relay with multi-layer gold contact, for mounting on DIN rail NS 35/7,5, 2 PDTs, input voltage 48 V DC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Relays

Additional Product Information

Dimensions
Width 14 mm
Height 80 mm
Depth 94 mm
Ambient conditions
Ambient temperature (operation) -40 °C ... 60 °C
Ambient temperature (storage/transport) -40 °C ... 85 °C
Coil side
Nominal input voltage UN 48 V DC
Typical input current at UN 20 mA
Typical response time 8 ms
Typical release time 10 ms

Protective circuit Protection against polarity reversal Polarity protection diode
Free-wheeling diode Damping diode
Operating voltage display Yellow LED
Power dissipation for nominal condition 0.96 W
Contact side
Contact type 2 PDT
Contact material AgNi, hard gold-plated
Maximum switching voltage 30 V AC
36 V DC
Minimum switching voltage 100 mV (at 10 mA)
Min. switching current 1 mA (at 24 V)
Maximum inrush current 50 mA
Limiting continuous current 50 mA
Interrupting rating (ohmic load) max. 1.2 W (at 24 V DC)
Note the following values are applicable if a gold layer is destroyed
Maximum switching voltage 250 V AC/DC
Minimum switching voltage 5 V AC/DC
Limiting continuous current 6 A
Maximum inrush current 15 A (300 ms)
Min. switching current 10 mA
Interrupting rating (ohmic load) max. 140 W (at 24 V DC)
85 W (at 48 V DC)
60 W (at 60 V DC)
44 W (at 110 V DC)
60 W (at 220 V DC)
1500 VA (for 250 V AC)
Switching capacity in acc. with DIN VDE 0660/IEC 60947 2 A (at 24 V, DC13)
0.2 A (at 110 V, DC13)
0.2 A (at 250 V, DC13)
2 A (at 24 V, AC15)
2 A (at 120 V, AC15)
2 A (at 250 V, AC15)
General
Operating mode 100% operating factor
Degree of protection RT III (Relay)
Mechanical service....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PLC-RPT-48DC/21-21AU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.