INDUSTRIAL COMPONENT DATA

PLC-RPT-120UC/21HC/EX 2909533 PHOENIX CONTACT Relay Module

Brand: PHOENIX CONTACT | Manufacturer Part Number: PLC-RPT-120UC/21HC/EX



Manufacturer	PHOENIX CONTACT
MPN / Reference	PLC-RPT-120UC/21HC/EX
Catalog number	2909533
Category	Switching relay
Minimum order	10 Pcs
Document ID	EO-3D27D19FBF
Generated	2026-11-19

Product Overview

Relay Module
PLC-INTERFACE, consisting of a base terminal block for mounting on a 14 mm rail with push-in connection and plug-in relay with 10 A power contact, 1 switched contact, input voltage of 120 V AC/110 V DC. Approved according to ATEX/IECEx (zone 2) and Ex zone class I, div. 2.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Relays

Additional Product Information

Key Commercial Data
Orderkey 2909533
Packing unit 10 pc
Minimum order quantity 10 pc
Note Made to Order (non-returnable)
Catalog page Page 459 (C-5-2017)
GTIN 4055626363707
Weight per Piece (excluding packing) 66.480 g
Custom tariff number 85364900
Country of origin DE (Germany)
Note
Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions
Width 14 mm
Height 80 mm
Depth 94 mm
Ambient conditions
Ambient temperature (operation) -20 °C ... 60 °C (UL)
-40 °C ... 60 °C (ATEX / IECEx)
Ambient temperature (storage/transport) -40 °C ... 85 °C
Coil side
Nominal input voltage UN 120 V AC
110 V DC
Typical input current at UN 4.5 mA
Typical response time 7 ms
Typical release time 10 ms
Protective circuit Bridge rectifier Bridge rectifier
Operating voltage display Yellow LED
Power dissipation for nominal condition 0.54 W
Contact side
Contact type 1 PDT
Type of switch contact Single contact
Contact material AgNi
Maximum switching voltage 250 V AC/DC (The separating plate PLC-ATP should be installed for voltages larger than 250 V (L1, L2, L3) between identical terminal blocks in adjacent modules. Potential bridging is then carried out with FBST 8-PLC... or ...FBST 500...)
Minimum switching voltage 12 V (at 10 mA)
Min. switching current 10 mA (at 12 V)
Maximum inrush current 30 A (300 ms)
Limiting continuous current 10 A
6 A (value applies to connections 12. If connections 12 are bridged, the normal value applies.)
Interrupting rating (ohm...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PLC-RPT-120UC/21HC/EX with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.