INDUSTRIAL COMPONENT DATA

PLC-RPT-230UC/21/SO46 2910110 PHOENIX CONTACT Relay Module

Brand: PHOENIX CONTACT | Manufacturer Part Number: PLC-RPT-230UC/21/SO46



Manufacturer	PHOENIX CONTACT
MPN / Reference	PLC-RPT-230UC/21/SO46
Catalog number	2910110
Category	Switching relay
Minimum order	1 Pcs
Document ID	EO-F2210BF73A
Generated	2026-11-19

Product Overview

Relay Module
PLC-INTERFACE against eddy currents and/or eddy voltages on the control side, consisting of PLC-BPT.../21 base terminal block with push-in connection and plug-in miniature relay with power contact, 1 switched contact, input voltage 230 V AC
PLC-INTERFACE against interference currents or interference voltages on the control side, consisting of PLC-BPT.../21 basic terminal block with push-in connection and miniature plug-in relay with power contact, 1 changeover contact, input voltage 230 V AC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Relays

Additional Product Information

Key Commercial Data
Orderkey 2910110
Packing unit 10 pc
GTIN 4055626426808
Weight per Piece (excluding packing) 31.270 g
Custom tariff number 85364900
Country of origin DE (Germany)
Note
Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions
Width 6.2 mm
Height 80 mm
Depth 94 mm
Ambient conditions
Ambient temperature (operation) -40 °C ... 55 °C
Ambient temperature (storage/transport) -40 °C ... 85 °C
Coil side
Nominal input voltage UN 230 V AC
220 V DC
Input voltage range in reference to UN 0.78 ... 1.14
Typical input current at UN 8.8 mA (50 Hz)
10 mA (60 Hz)
Typical response time 7 ms
Typical release time 20 ms
Protective circuit Bridge rectifier
RCZ filter
Status display Yellow LED
Power dissipation for nominal condition 2.3 W
Contact side
Contact type 1 PDT
Type of switch contact Single contact
Contact material AgSnO
Maximum switching voltage 250 V AC/DC (The separating plate PLC-ATP should be installed for voltages larger than 250 V (L1, L2, L3) between identical terminal blocks in adjacent modules. Potential bridging is then carried out with FBST 8-PLC... or ...FBST 500...)
Minimum switching voltage 5 V (at 100 mA)
Min. switching current 10 mA (at 12 V)
Limiting continuous current 6 A
Interrupting rating (ohmic load) max. 140 W (at 24 V DC)
20 W (at 48 V DC)
18 W (at 60 V DC)
23 W (at 110 V DC)
40 W (at 220 V DC)
1500 VA (for 250 V AC)
Switching capacity 2 A (at 24 V, DC13)
0.2 A (at 110 V, DC13)
0.1 A (at 220 V, D...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PLC-RPT-230UC/21/SO46 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.