INDUSTRIAL COMPONENT DATA

# PLC-RSC-220DC/21AU 2987286 PHOENIX CONTACT Relay Module

**Brand: PHOENIX CONTACT | Manufacturer Part Number: PLC-RSC-220DC/21AU**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | PLC-RSC-220DC/21AU |
| Catalog number | 2987286 |
| Category | Switching relay |
| Minimum order | 1 Pcs |
| Document ID | EO-A6047A520B |
| Generated | 2026-11-19 |

## Product Overview

Relay Module
PLC-INTERFACE, consisting of PLC-BSC.../21 base terminal block with screw connection and plug-in miniature relay with multi-layer gold contact, for mounting on NS 35/7.5 rail, 1 switched contact, input voltage 220 V DC

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Industrial Relays |

## Additional Product Information

Key Commercial Data
Orderkey 2987286
Packing unit 10 pc
Note Made to Order (non-returnable)
GTIN 4046356337267
Weight per Piece (excluding packing) 27.580 g
Custom tariff number 85364900
Country of origin DE (Germany)
Note
Utilization restriction EMC: class A product, see manufacturer's declaration in the download area
Dimensions
Width 6.2 mm
Height 80 mm

Depth 94 mm
Ambient conditions
Ambient temperature (operation) -25 °C ... 55 °C
Ambient temperature (storage/transport) -40 °C ... 85 °C
Coil side
Nominal input voltage UN 220 V DC
Typical input current at UN 3 mA
Typical response time 7 ms
Typical release time 15 ms
Coil voltage 60 V DC
Protective circuit Reverse polarity protection Polarity protection diode
Surge protection Damping diode
Operating voltage display Yellow LED
Power dissipation for nominal condition 0.66 W
Contact side
Contact type 1 PDT
Type of switch contact Single contact
Contact material AgSnO, hard gold-plated
Maximum switching voltage 30 V AC
36 V DC
Minimum switching voltage 100 mV (at 10 mA)
Min. switching current 1 mA (at 24 V)
Maximum inrush current 50 mA
Limiting continuous current 50 mA
Interrupting rating (ohmic load) max. 1.2 W (at 24 V DC)
Contact side (with destroyed gold layer)
Note the following values are applicable if a gold layer is destroyed
Maximum switching voltage 250 V AC/DC
Minimum switching voltage 5 V (at 100 mA)
Min. switching current 10 mA (at 12 V)
Connection data input side
Connection name Coil side
Connection method Screw co...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PLC-RSC-220DC/21AU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.



Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.