

INDUSTRIAL COMPONENT DATA

PLH 5/ 3-7,5-ZF MCRD/WH/BK 1713573 PHOENIX CONTACT

Terminal for printed circuit board, nominal current: 41 A..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PLH 5/ 3-7,5-ZF MCRD/WH/BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	PLH 5/ 3-7,5-ZF MCRD/WH/BK
Catalog number	1713573
Category	Printed circuit board terminal
Minimum order	25 Pcs
Document ID	EO-7260045C47
Generated	2026-09-29

Product Overview

Terminal for printed circuit board, nominal current: 41 A, rated voltage: 1000 V, pitch: 7.5 mm, number of poles: 3, type of connection: Connection by spring loaded push lock, direction of connection conductor/pcb: 0 °, color: multicolor

Terminal block for printed circuit board, nominal current: 41 A, dimensioning voltage (III/2): 1000 V, nominal cross-section: 6 mm², Number of potentials: 3, Number of rows: 1, Number of poles per row: 3, article family: PLH 5/, pitch: 7.5 mm, connection type: Spring push lock connection, mounting: Wave soldering, conductor connection direction/printed circuit board: 0°, Color: Multicolor, Packing Type: Boxed Packed

Printed circuit board terminal, rated current: 41 A, rated voltage (III/2): 1000 V, rated cross-section: 6 mm², number of potentials: 3, number of rows: 1, number of poles per row: 3, article family: PLH 5/, pitch: 7.5 mm, connection type: Push lock spring connection, mounting: Wave soldering, conductor connection direction/printed circuit board: 0°, color: multicolor, Pin arrangement: Zigzag M pins, number of solder pins per potential: 1, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Technical dataItem PropertiesProduct Type Printed Circuit Board Terminal

Product Family PLH 5/

Product Line COMBICON Terminals L

Number of poles 3

Step 7.5 mm

Number of connections 3

Number of rows 1
Number of potentials 3
Pin Design M zigzag pins
Number of Solder Pins Per Potential 1
Data Maintenance Status
Article Review 02
Electrical PropertiesNominal Current IN 41 A
Nominal voltage UN 1000 V
Sizing voltage (III/3) 1000 V
Dimensioning transient voltage (III/3) 8 kV
Dimensioning voltage (III/2) 1000 V
Dimensioning Transient Voltage (III/2) 8 kV
Nominal voltage (II/2) 1000 V
Dimensioning transient voltage (II/2) 6 kV
Connection dataConnection technology
Nominal Section 6 mm²
Connecting Conductors
Connection type Push lock spring connection
Connection direction of the conductor with respect to the plug direction 0 °
Rigid conductor section 0.2 mm² ... 6 mm²
Flexible conductor section 0.2 mm² ... 6 mm²
AWG Conductor Section 24 ... 10
Flexible conductor section with toe cap, without plastic sleeve 0.2 mm² ... 6 mm²
Flexible conductor section with toe cap, with plastic sleeve 0.2 mm² ... 6 mm²
2 conductors with the same cross-section, flexible with TWIN toe cap with plastic sleeve 0.5 mm² ... 2.5 mm²
Peel Length 12 mm
assemblyType of mounting Wave soldering
Pin Design M zigzag pins
Material DataMaterial data - contact
Observation WEEE/RoHS compliant, filament-free according to IEC 60068-2-82/JEDEC JESD 201
Contact material Cu Alloy
Surface Characteristics Galvanically tinned
Me...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PLH 5/ 3-7,5-ZF MCRD/WH/BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.