
INDUSTRIAL COMPONENT DATA

FK-MCP 1,5/12-ST-3,81-LR 1817521 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: FK-MCP 1,5/12-ST-3,81-LR



Manufacturer	PHOENIX CONTACT
MPN / Reference	FK-MCP 1,5/12-ST-3,81-LR
Catalog number	1817521
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-BC6A4DF6EF
Generated	2026-11-19

Product Overview

Printed-circuit board connector
Connector for printed circuit board, nominal section: 1.5 mm², color: green, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Female, number of potentials: 12, number of rows: 1, number of poles: 12, number of connections: 12, family of articles: FK-MCP 1.5/.. -ST-LR, pitch: 3.81 mm, connection type: Push-in spring connection, driver/printed circuit board connection direction: 0 °, plug-in system: COMBICON MC 1.5, lock: Snap lock, fixing type: Lock & Release extractor lever, packaging type: boxed
Conductive plate connector, nominal cross-section: 1.5 mm2, colour: green, nominal current: 8 A, reference voltage (III/2): 160 V, contact area: Sn, contact type: Female connector, number of potentials: 12, number of rows: 1, number of poles: 12, number of connections: 12, item range: FK-MCP 1.5/.. -ST-LR, pitch: 3.81 mm, connection type: Push-in spring connection, conductor/PCB plugging direction: 0°, Plug-in system: COMBICON MC 1.5, Locking: Locking and unlocking, Fastening type: Lock and Release ejection lever, Packaging type: packed in a carton

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1817521
Packing unit 50 pc
Catalog page Page 199 (C-1-2013)
GTIN 4046356756860

Weight per Piece (excluding packing) 11.730 g
Custom tariff number 85366990
Country of origin DE (Germany)
Dimensions
Length [l] 27.4 mm
Width [w] 52.65 mm
Height [h] 14.22 mm
Pitch 3.81 mm
Dimension a 41.91 mm
General
Range of articles FK-MCP 1,5/..-ST-LR
Number of positions 12
Connection method Push-in spring connection
Insulating material group I
Rated surge voltage (III/3) 2.5 kV
Rated surge voltage (III/2) 2.5 kV
Rated surge voltage (II/2) 2.5 kV
Rated voltage (III/3) 160 V
Rated voltage (III/2) 160 V
Rated voltage (II/2) 320 V
Connection in acc. with standard EN-VDE
Nominal current IN 8 A
Nominal cross section 1.5 mm²
Maximum load current 8 A (with 1.5 mm² conductor cross section)
Insulating material PA
Flammability rating according to UL 94 V0
Internal cylindrical gage A1
Stripping length 9 mm
Connection data
Conductor cross section solid min. 0.14 mm²
Conductor cross section solid max. 1.5 mm²
Conductor cross section flexible min. 0.14 mm²
Conductor cross section flexible max. 1.5 mm²
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 1.5 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 0.75 mm²
Conductor cross section AWG min. 26
Conductor cr...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FK-MCP 1,5/12-ST-3,81-LR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.