
INDUSTRIAL COMPONENT DATA

DFK-PC 5/ 6-ST-7,62 1716548 PHOENIX CONTACT Durchführungsstecker

Brand: PHOENIX CONTACT | Manufacturer Part Number: DFK-PC 5/ 6-ST-7,62



Manufacturer	PHOENIX CONTACT
MPN / Reference	DFK-PC 5/ 6-ST-7,62
Catalog number	1716548
Category	Cable connector
Minimum order	10 Pcs
Document ID	EO-B5281D0C29
Generated	2026-11-18

Product Overview

Durchführungsstecker
Wall pass block, nominal section: 6 mm², color: green, nominal current: 41 A, nominal voltage (III/2): 1000 V, contact surface: Tin, contact type: Male, number of potentials: 6, number of rows: 1, number of poles: 6, number of connections: 6, family of articles: DFK-PC 5/.. -ST, pitch: 7.62 mm, connection type: Screw connection with traction capsule, screw clamping form: Z1L Pozidriv with longitudinal slot, driver/printed circuit board connection direction: 0 °, plug-in system: COMBICON PC 5, Plug-in face orientation: Standard, lock: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1716548
Packing unit 10 pc
Minimum order quantity 10 pc
Catalog page Page 548 (C-1-2013)
GTIN 4046356137164
Weight per Piece (excluding packing) 35.000 g
Custom tariff number 85366990
Country of origin PL (Poland)
Dimensions

Length [l] 48.93 mm
Width [w] 71.22 mm
Height [h] 26.24 mm
Pitch 7.62 mm
Dimension a 38.1 mm
General
Range of articles DFK-PC 5/..-ST
Number of positions 6
Connection method Screw connection with tension sleeve
Insulating material group I
Rated surge voltage (III/3) 8 kV
Rated surge voltage (III/2) 8 kV
Rated surge voltage (II/2) 6 kV
Rated voltage (III/3) 630 V
Rated voltage (III/2) 1000 V
Rated voltage (II/2) 1000 V
Connection in acc. with standard EN-VDE
Nominal current IN 41 A
Nominal cross section 6 mm²
Maximum load current 41 A
Insulating material PA
Flammability rating according to UL 94 V0
Stripping length 10 mm
Screw thread M3
Tightening torque, min 0.7 Nm
Tightening torque max 0.8 Nm
Connection data
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 10 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 6 mm²
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 6 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 4 mm²
Conductor cross secti...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DFK-PC 5/ 6-ST-7,62 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.