
INDUSTRIAL COMPONENT DATA

FMC 1,5/16-ST-3,5-RF 1952160 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: FMC 1,5/16-ST-3,5-RF



Manufacturer	PHOENIX CONTACT
MPN / Reference	FMC 1,5/16-ST-3,5-RF
Catalog number	1952160
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-9FA8DEC6DA
Generated	2026-11-18

Product Overview

Printed-circuit board connector
Connector for printed circuit board, nominal section: 1.5 mm², color: green, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Female, number of potentials: 16, number of rows: 1, number of poles: 16, number of connections: 16, family of articles: FMC 1.5/.. -ST-RF, pitch: 3.5mm, connection type: Push-in spring connection, driver/printed circuit board connection direction: 0°, plug-in system: COMBICON MC 1.5, lock: Snap-in lock, fixing type: Snap flange, packing type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1952160
Packing unit 50 pc
Minimum order quantity 50 pc
Catalog page Page 201 (C-1-2013)
GTIN 4017918942809
Weight per Piece (excluding packing) 8.890 g
Custom tariff number 85366990
Country of origin DE (Germany)
Dimensions

Length [l] 22.9 mm
Width [w] 66.1 mm
Height [h] 7.8 mm
Pitch 3.5 mm
Dimension a 52.5 mm
General
Range of articles FMC 1,5/..-ST-RF
Number of positions 16
Connection method Push-in spring connection
Insulating material group I
Rated surge voltage (III/3) 2.5 kV
Rated surge voltage (III/2) 2.5 kV
Rated surge voltage (II/2) 2.5 kV
Rated voltage (III/3) 160 V
Rated voltage (III/2) 160 V
Rated voltage (II/2) 320 V
Connection in acc. with standard EN-VDE
Nominal current IN 8 A
Nominal cross section 1.5 mm²
Maximum load current 8 A
Insulating material PA
Flammability rating according to UL 94 V0
Internal cylindrical gage A1
Stripping length 10 mm
Connection data
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 1.5 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 1.5 mm²
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 1.5 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 0.75 mm²
Conductor cross section AWG min. 24
Conductor cross section AWG max....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FMC 1,5/16-ST-3,5-RF with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.