
INDUSTRIAL COMPONENT DATA

GIC 2,5 HCV/11-ST-7,62 1745713 PHOENIX CONTACT Plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: GIC 2,5 HCV/11-ST-7,62



Manufacturer	PHOENIX CONTACT
MPN / Reference	GIC 2,5 HCV/11-ST-7,62
Catalog number	1745713
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-135F91B5A0
Generated	2026-11-19

Product Overview

Plug
Connector for printed circuit board, nominal section: 2.5 mm², color: green, nominal current: 16 A, nominal voltage (III/2): 1000 V, contact surface: Tin, contact type: Male, number of potentials: 11, number of rows: 1, number of poles: 11, number of connections: 11, article family: GIC 2.5 HCV/.. -ST, pitch: 7.62 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal groove, connection direction conductor/printed circuit board: 0 °, clamping hook: - without clamping hook, plug-in system: COMBICON MSTB 2.5 HC, locking: without, fixing type: without, packaging type: boxed
Conductive plate connector, nominal cross-section: 2.5 mm2, colour: green, nominal current: 16 A, reference voltage (III/2): 1000 V, contact area: Sn, contact type: Male, number of potentials: 11, number of rows: 1, number of poles: 11, number of connections: 11, article range: GIC 2.5 HCV/.. -ST, pitch: 7.62 mm, connection type: Screw connection with ring, screw driving surface: L Longitudinal slot, conductor/PCB plugging direction: 0°, locking clip: - without locking clip, plug-in system: COMBICON MSTB 2.5 HC, locking: without, fastening type: without, packaging type: packed in carton

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1745713
Packing unit 50 pc
Minimum order quantity 50 pc
Note Made to Order (non-returnable)

Catalog page Page 503 (C-1-2013)
GTIN 4046356309868
Weight per Piece (excluding packing) 22.220 g
Custom tariff number 85366990
Country of origin SK (Slovakia)
Dimensions
Length [l] 22.8 mm
Width [w] 83.6 mm
Height [h] 17.5 mm
Pitch 7.62 mm
Dimension a 76.2 mm
General
Range of articles GIC 2,5 HCV/..-ST
Number of positions 11
Connection method Screw connection with tension sleeve
Insulating material group I
Rated surge voltage (III/3) 8 kV
Rated surge voltage (III/2) 8 kV
Rated surge voltage (II/2) 8 kV
Rated voltage (III/3) 1000 V
Rated voltage (III/2) 1000 V
Rated voltage (II/2) 1000 V
Connection in acc. with standard EN-VDE
Nominal current IN 16 A
Nominal cross section 2.5 mm²
Maximum load current 16 A
Insulating material PA
Flammability rating according to UL 94 V0
Internal cylindrical gage A3
Stripping length 8 mm
Screw thread M3
Tightening torque, min 0.5 Nm
Tightening torque max 0.6 Nm
Connection data
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 2.5 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 2.5 mm²
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²
Conductor cross section....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / GIC 2,5 HCV/11-ST-7,62 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.