
INDUSTRIAL COMPONENT DATA

MC 1,5/12-ST1F-5,08 1900989 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: MC 1,5/12-ST1F-5,08



Manufacturer	PHOENIX CONTACT
MPN / Reference	MC 1,5/12-ST1F-5,08
Catalog number	1900989
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-1558BDA289
Generated	2026-11-19

Product Overview

Printed-circuit board connector
Connector for printed circuit board, nominal section: 1.5 mm², color: green, nominal current: 8 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Female, number of potentials: 12, number of rows: 1, number of poles: 12, number of connections: 12, family of articles: MC 1.5/.. -ST1F, pitch: 5.08 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, conductor/printed circuit board connection direction: 0 °, plug-in system: COMBICON MC 1.5, locking: Screw locking, fixing type: Air clamping (screw), packaging type: boxed
PCB connector, nominal cross-section: 1.5 mm2, color: green, rated current: 8 A, rated voltage (III/2): 320 V, contact surface: Sn, contact type: socket, number of potentials: 12, number of rows: 1, number of poles: 12, number of terminals: 12, article family: MC 1,5/.. -ST1F, Pitch: 5.08 mm, Connection type: Screw connection with pull sleeve, Screw attack shape: L Longitudinal slot, Connection direction conductor/board: 0 °, Plug-in system: COMBICON MC 1.5, Locking: Screw lock, Fastening type: Screw flange, Packaging type: packed in carton

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1900989
Packing unit 50 pc
Minimum order quantity 50 pc
Catalog page Page 247 (C-1-2013)

GTIN 4017918429386
Weight per Piece (excluding packing) 9.780 g
Custom tariff number 85366990
Country of origin DE (Germany)
Dimensions
Length [l] 15.5 mm
Width [w] 70.08 mm
Height [h] 11.1 mm
Pitch 5.08 mm
Dimension a 55.88 mm
General
Range of articles MC 1,5/..-ST1F
Number of positions 12
Connection method Screw connection with tension sleeve
Insulating material group I
Rated surge voltage (III/3) 4 kV
Rated surge voltage (III/2) 4 kV
Rated surge voltage (II/2) 4 kV
Rated voltage (III/3) 250 V
Rated voltage (III/2) 320 V
Rated voltage (II/2) 630 V
Connection in acc. with standard EN-VDE
Nominal current IN 8 A
Nominal cross section 1.5 mm²
Maximum load current 8 A (with 1.5 mm² conductor cross section)
Insulating material PA
Flammability rating according to UL 94 V0
Internal cylindrical gage A1
Stripping length 7 mm
Screw thread M2
Tightening torque, min 0.22 Nm
Tightening torque max 0.25 Nm
Connection data
Conductor cross section solid min. 0.14 mm²
Conductor cross section solid max. 1.5 mm²
Conductor cross section flexible min. 0.14 mm²
Conductor cross section flexible max. 1.5 mm²
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 1.5 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²
Conductor cross section f...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MC 1,5/12-ST1F-5,08 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.