INDUSTRIAL COMPONENT DATA

MSTB 2,5/ 2-ST 1754449 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: MSTB 2,5/ 2-ST



Manufacturer	PHOENIX CONTACT
MPN / Reference	MSTB 2,5/ 2-ST
Catalog number	1754449
Category	Cable connector
Minimum order	100 Pcs
Document ID	EO-1CDB56A34B
Generated	2026-11-18

Product Overview

Printed-circuit board connector
Connector for printed circuit board, nominal section: 2.5 mm², color: green, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Female, number of potentials: 2, number of rows: 1, number of poles: 2, number of connections: 2, article family: MSTB 2.5/.. -ST, pitch: 5 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, conductor/printed circuit board connection direction: 0 °, clamping hook: - Clamping hook, plug-in system: COMBICON MSTB 2.5, locking: without, fixing type: without, packaging type: boxed
PCB connector, nominal cross-section: 2.5 mm2, colour: green, rated current: 12 A, dimensioning voltage (III/2): 320 V, contact surface: Sn, contact connection type: Female, number of potentials: 2, number of rows: 1, number of poles: 2, number of connections: 2, product series: MSTB 2.5/.. -ST, pitch: 5 mm, connection type: Screw connection with cage, screw attachment form: L Longitudinal slot, conductor/board connection direction: 0 °, locking hook: - Locking hook, plug system: COMBICON MSTB 2.5, locking: none, fixing type: none, packaging type: packed in carton

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1754449
Packing unit 100 pc
Minimum order quantity 100 pc
Catalog page Page 262 (C-1-2013)

GTIN 4017918028619
Weight per Piece (excluding packing) 3.440 g
Custom tariff number 85366990
Country of origin DE (Germany)
Item properties
Brief article description Printed-circuit board connector
Plug-in system CLASSIC COMBICON
Type of contact Female connector
Range of articles MSTB 2,5/..-ST
Pitch 5 mm
Number of positions 2
Connection method Screw connection with tension sleeve
Drive form screw head Slotted (L)
Screw thread M3
Locking without
Number of levels 1
Number of connections 2
Number of potentials 2
Electrical parameters
Rated current 12 A
Rated insulation voltage (III/2) 320 V
Rated surge voltage (III/2) 4 kV
Connection capacity
Conductor cross section solid 0.2 mm² ... 2.5 mm²
Conductor cross section flexible 0.2 mm² ... 2.5 mm²
Conductor cross section AWG / kcmil 24 ... 12
Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm² ... 2.5 mm²
Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm² ... 2.5 mm²
2 conductors with same cross section, solid 0.2 mm² ... 1 mm²
2 conductors with same cross section, flexible 0.2 mm² ... 1.5 mm²
2 conductors with same cross section, stranded, ferrules without plastic sleeve 0.25 mm² ... 1 mm²
2 conductors with same cross section, stranded, with TWIN ferrules with plastic sleeve 0.5 mm² ... 1.5 mm²
Cylindrical gauge a x b / diameter 2.8 mm x 2.4 mm / 2.5 mm
Stri...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MSTB 2,5/ 2-ST with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.