
INDUSTRIAL COMPONENT DATA

PC 35 HC/ 4-STF-SH-15,00 1762848 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: PC 35 HC/ 4-STF-SH-15,00



Manufacturer	PHOENIX CONTACT
MPN / Reference	PC 35 HC/ 4-STF-SH-15,00
Catalog number	1762848
Category	Cable connector
Minimum order	10 Pcs
Document ID	EO-719EDA7D32
Generated	2026-11-18

Product Overview

Printed-circuit board connector
Connector for printed circuit board, nominal section: 35 mm², color: green, nominal current: 125 A, nominal voltage (III/2): 1000 V, contact surface: silver, contact type: Female, number of potentials: 4, number of rows: 1, number of poles: 4, number of connections: 4, family of articles: PC 35 HC/.. -STF-SH, pitch: 15 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, conductor/printed circuit board connection direction: 0 °, clamping hook: - without clamping hook, plug-in system: COMBICON PC 35, locking: Screw lock, fixing type: Air clamping (screw), packaging type: Boxed Packaging

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1762848
Packing unit 10 pc
Minimum order quantity 10 pc
Note Made to Order (non-returnable)
Catalog page Page 587 (C-1-2013)
GTIN 4046356460743
Weight per Piece (excluding packing) 200.000 g
Custom tariff number 85366990

Country of origin PL (Poland)
Dimensions
Length [l] 52 mm
Width [w] 84.4 mm
Height [h] 42.5 mm
Pitch 15 mm
Dimension a 45 mm
General
Range of articles PC 35 HC/..-STF-SH
Number of positions 4
Connection method Screw connection with tension sleeve
Insulating material group I
Rated surge voltage (III/3) 8 kV
Rated surge voltage (III/2) 8 kV
Rated surge voltage (II/2) 8 kV
Rated voltage (III/3) 1000 V
Rated voltage (III/2) 1000 V
Rated voltage (II/2) 1000 V
Connection in acc. with standard EN-VDE
Nominal current IN 125 A
Nominal cross section 35 mm²
Maximum load current 125 A
Insulating material PA
Flammability rating according to UL 94 V0
Stripping length 20 mm
Screw thread M5
Tightening torque, min 2.5 Nm
Tightening torque max 4.5 Nm
Note Tightening torque <= 25 mm² is 2.5 Nm, > 25 mm² is 4.5 Nm
Connection data
Conductor cross section solid min. 0.5 mm²
Conductor cross section solid max. 35 mm²
Conductor cross section flexible min. 0.5 mm²
Conductor cross section flexible max. 35 mm²
Conductor cross section flexible, with ferrule without plastic sleeve min. 1 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 35 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 1.5 mm²
Con...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PC 35 HC/ 4-STF-SH-15,00 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.