
INDUSTRIAL COMPONENT DATA

PC 5/ 7-STCL1-7,62 1778117 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: PC 5/ 7-STCL1-7,62



Manufacturer	PHOENIX CONTACT
MPN / Reference	PC 5/ 7-STCL1-7,62
Catalog number	1778117
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-35C088D074
Generated	2026-11-18

Product Overview

Printed-circuit board connector
Connector for printed circuit board, nominal section: 6 mm², color: green, nominal current: 41 A, nominal voltage (III/2): 1000 V, contact surface: Tin, contact type: Female, number of potentials: 7, number of rows: 1, number of poles: 7, number of connections: 7, family of articles: PC 5/.. -STCL1, pitch: 7.62 mm, connection type: Screw connection with traction capsule, screw clamping form: H1L Philipps-Recess with longitudinal slot, connection direction conductor/printed circuit board: 0 °, clamping hook: - without clamping hook, plug-in system: COMBICON PC 5, locking: Clip lock, fixing type: Click & Lock locking clamp, Packaging Type: Boxed Packaging

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1778117
Packing unit 50 pc
Minimum order quantity 50 pc
Catalog page Page 525 (C-1-2013)
GTIN 4046356523240
Weight per Piece (excluding packing) 30.590 g
Custom tariff number 85366990
Country of origin DE (Germany)

Dimensions
Length [l] 35.3 mm
Width [w] 61.49 mm
Height [h] 19.7 mm
Pitch 7.62 mm
Dimension a 45.72 mm
General
Range of articles PC 5/..-STCL1
Number of positions 7
Connection method Screw connection with tension sleeve
Insulating material group I
Rated surge voltage (III/3) 8 kV
Rated surge voltage (III/2) 8 kV
Rated surge voltage (II/2) 6 kV
Rated voltage (III/3) 1000 V
Rated voltage (III/2) 1000 V
Rated voltage (II/2) 1000 V
Nominal current IN 41 A
Nominal cross section 6 mm²
Maximum load current 41 A
Insulating material PA
Flammability rating according to UL 94 V0
Internal cylindrical gage A4
Stripping length 10 mm
Screw thread M3
Tightening torque, min 0.5 Nm
Tightening torque max 0.8 Nm
Note Tightening torque <= 4 mm² is 0.5 Nm to 0.6 Nm,> 4 mm² is 0.7 Nm to 0.8 Nm
Connection data
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 10 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 6 mm²
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 6 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²
Conductor cross section flexibl...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PC 5/ 7-STCL1-7,62 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.