INDUSTRIAL COMPONENT DATA

# PT 1,5/ 2-PH-5,0 CLIP 1755732 PHOENIX CONTACT PCB terminal block

**Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 1,5/ 2-PH-5,0 CLIP**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | PT 1,5/ 2-PH-5,0 CLIP |
| Catalog number | 1755732 |
| Category | Cable connector |
| Minimum order | 250 Pcs |
| Document ID | EO-A116AF1920 |
| Generated | 2026-11-18 |

## Product Overview

PCB terminal block
Connector for printed circuit board, nominal section: 1.5 mm², color: green, nominal current: 10 A, nominal voltage (III/2): 400 V, contact surface: Tin, contact type: Female, number of potentials: 2, number of rows: 1, number of poles: 2, number of connections: 2, family of articles: PT 1.5/.. -PH CLIP, pitch: 5 mm, connection type: Screw connection with traction capsule, screw clamping method: H1L Philipps-Recess with longitudinal groove, conductor connection direction/printed circuit board: 0 °, plug-in system: COMBICON PST 1.3, lock: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > PCB Connectors (PCC) |

## Additional Product Information

Key Commercial Data
Orderkey 1755732
Packing unit 250 pc
Catalog page Page 425 (C-1-2013)
GTIN 4046356334914
Weight per Piece (excluding packing) 2.090 g
Custom tariff number 85366990
Country of origin CN (China)
Dimensions
Length [ l ] 14.7 mm

Width [ w ] 10 mm
Height [ h ] 12.3 mm
Pitch 5 mm
Dimension a 5 mm
General
Range of articles PT 1,5/..-PH CLIP
Number of positions 2
Connection method Screw connection with tension sleeve
Insulating material group I
Rated surge voltage (III/3) 4 kV
Rated surge voltage (III/2) 4 kV
Rated surge voltage (II/2) 4 kV
Rated voltage (III/3) 250 V
Rated voltage (III/2) 400 V
Rated voltage (II/2) 630 V
Connection in acc. with standard EN-VDE
Nominal current IN 10 A
Nominal cross section 1.5 mm²
Maximum load current 10 A
Insulating material PA
Flammability rating according to UL 94 V0
Stripping length 6 mm
Tightening torque, min 0.35 Nm
Tightening torque max 0.4 Nm
Connection data
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 1.5 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 1.5 mm²
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 1 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 1 mm²
Conductor cross section AWG min. 26
Conductor cross section AWG max. 14....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 1,5/ 2-PH-5,0 CLIP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.