INDUSTRIAL COMPONENT DATA

QC 1,5/ 3-STF 1718122 PHOENIX CONTACT Plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: QC 1,5/ 3-STF



Manufacturer	PHOENIX CONTACT
MPN / Reference	QC 1,5/ 3-STF
Catalog number	1718122
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-421E5C80B3
Generated	2026-11-18

Product Overview

Plug
Connector for printed circuit board, nominal section: 1.5 mm², color: green, nominal current: 12 A, nominal voltage (III/2): 630 V, contact surface: Tin, contact type: Female, number of potentials: 3, number of rows: 1, number of poles: 3, number of connections: 3, family of articles: QC 1.5/.. -STF, pitch: 5 mm, connection type: Offset connection, conductor/printed circuit board connection direction: 0 °, clamping hook: - without clamping hook, plug-in system: COMBICON MSTB 2.5, locking: Screw locking, fixing type: Air clamping (screw), packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1718122
Packing unit 50 pc
Minimum order quantity 50 pc
Note Made to Order (non-returnable)
Catalog page Page 293 (C-1-2013)
GTIN 4046356140393
Weight per Piece (excluding packing) 9.890 g
Custom tariff number 85366990
Country of origin CN (China)
Dimensions

Length [l] 33.4 mm
Width [w] 24.9 mm
Height [h] 19.6 mm
Pitch 5 mm
Dimension a 10 mm
General
Range of articles QC 1,5/..-STF
Number of positions 3
Connection method Displacement connection
Insulating material group I
Rated surge voltage (III/3) 4 kV
Rated surge voltage (III/2) 4 kV
Rated surge voltage (II/2) 4 kV
Rated voltage (III/3) 500 V
Rated voltage (III/2) 630 V
Rated voltage (II/2) 1000 V
Connection in acc. with standard EN-VDE
Nominal current IN 12 A
Nominal cross section 1.5 mm²
Maximum load current 12 A
Insulating material PA
Flammability rating according to UL 94 V0
Connection data
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 1.5 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 1.5 mm²
Conductor cross section AWG min. 24
Conductor cross section AWG max. 16
Minimum AWG according to UL/CUL 24
Maximum AWG according to UL/CUL 16
Wire diameter incl. insulation 3 mm
Standards and Regulations
Connection in acc. with standard EN-VDE
CUL
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above thresho...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / QC 1,5/ 3-STF with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.