INDUSTRIAL COMPONENT DATA

VAL-SEC-T2-2C-350-FM 2905337 VAL-CP-2C-350 2859589 PHOENIX CONTACT Type 2 surge arrester

Brand: PHOENIX CONTACT | Manufacturer Part Number: VAL-SEC-T2-2C-350-FM



Manufacturer	PHOENIX CONTACT
MPN / Reference	VAL-SEC-T2-2C-350-FM
Catalog number	VAL-CP-2C-350 2859589
Category	Surge protection device for power supply systems
Minimum order	1 Pcs
Document ID	EO-02D4EFFA5C
Generated	2026-11-19

Product Overview

Type 2 surge arrester
Plug-in surge arrester according to type 2/class II, for two-phase power supply networks with PE and N routing combined in one conductor (3-conductor system: L1, L2, PEN), with remote indication contact.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Trabtech (TT)

Additional Product Information

Key Commercial Data
Orderkey 2905337
Packing unit 1 pc
Catalog page Page 47 (C-4-2017)
GTIN 4046356948005
Weight per Piece (excluding packing) 231.200 g
Custom tariff number 85363030
Country of origin DE (Germany)
Dimensions
Height 97.9 mm
Width 25.4 mm
Depth 74.5 mm (incl. DIN rail 7.5 mm)
Horizontal pitch 1.4 Div.

Ambient conditions
Degree of protection IP20
Ambient temperature (operation) -40 °C ... 80 °C
Ambient temperature (storage/transport) -40 °C ... 80 °C
Altitude <= 2000 m (amsl (above mean sea level))
Permissible humidity (operation) 5 % ... 95 %
Shock (operation) 30g (Half-sine / 11 ms / 3x ±X, ±Y, ±Z)
Vibration (operation) 5g (10 ... 500 Hz / 2.5 h / X, Y, Z)
General
IEC test classification II
T2
EN type T2
IEC power supply system TN-C
Mode of protection L-PEN
Mounting type DIN rail: 35 mm
Color light grey RAL 7035
traffic grey A RAL 7042
Housing material PA 6.6-FR 20% GF
PBT-FR
Degree of pollution 2
Flammability rating according to UL 94 V-0
Type DIN rail module, two-section, divisible
Number of positions 2
Surge protection fault message Optical, remote indicator contact
Protective circuit
Nominal voltage UN 240/415 V AC (TN-C)
Nominal frequency fN 50 Hz (60 Hz)
Maximum continuous voltage UC 350 V AC
Rated load current IL 40 A (Biconnect M4 fork-type cable lug 6 mm²)
63 A (TWIN ferrule 2 x 10 mm²)
Nominal discharge current In(8/20) µs 20 kA
Maximum discharge current Imax(8/20) µs 40 kA
Short-circuit current rating ISCCR 25 kA (in case of 315 A gG backup fuse)
5...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VAL-SEC-T2-2C-350-FM with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.