INDUSTRIAL COMPONENT DATA

# VAL-SEC-T2-3S-350 2905345 VAL-CP-3S-350/O 2881010 PHOENIX CONTACT Type 2 surge arrester

**Brand: PHOENIX CONTACT | Manufacturer Part Number: VAL-SEC-T2-3S-350**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | VAL-SEC-T2-3S-350 |
| Catalog number | VAL-CP-3S-350/O 2881010 |
| Category | Surge protection device for power supply systems |
| Minimum order | 1 Pcs |
| Document ID | EO-9E485C8421 |
| Generated | 2026-11-19 |

## Product Overview

Type 2 surge arrester
Plug-in surge arrester according to type 2/class II, for three-phase power supply networks with separate N and PE (5-conductor system: L1, L2, L3, N, PE).

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Trabtech (TT) |

## Additional Product Information

Key Commercial Data
Orderkey 2905345
Packing unit 1 pc
Catalog page Page 46 (C-4-2017)
GTIN 4046356948012
Weight per Piece (excluding packing) 390.600 g
Custom tariff number 85363030
Country of origin DE (Germany)
Dimensions
Height 89.9 mm
Width 49.2 mm
Depth 74.5 mm (incl. DIN rail 7.5 mm)
Horizontal pitch 2.7 Div.

Ambient conditions
Degree of protection IP20
Ambient temperature (operation) -40 °C ... 80 °C
Ambient temperature (storage/transport) -40 °C ... 80 °C
Altitude <= 2000 m (amsl (above mean sea level))
Permissible humidity (operation) 5 % ... 95 %
Shock (operation) 30g (Half-sine / 11 ms / 3x ±X, ±Y, ±Z)
Vibration (operation) 5g (10 ... 500 Hz / 2.5 h / X, Y, Z)
General
IEC test classification II
T2
EN type T2
IEC power supply system TN-S
TT
Mode of protection L-N
L-PE
N-PE
Mounting type DIN rail: 35 mm
Color light grey RAL 7035
traffic grey A RAL 7042
Housing material PA 6.6-FR 20% GF
PBT-FR
Degree of pollution 2
Flammability rating according to UL 94 V-0
Type DIN rail module, two-section, divisible
Number of positions 4
Surge protection fault message optical
Protective circuit
Nominal voltage UN 240/415 V AC (TN-S)
240/415 V AC (TT)
Nominal frequency fN 50 Hz (60 Hz)
Maximum continuous operating voltage UC(L-N) 350 V AC
Maximum continuous operating voltage UC(L-PE) 350 V AC
Maximum continuous voltage UC(N-PE) 264 V AC
Rated load current IL 40 A (Biconnect M4 fork-type cable lug 6 mm²)
63 A (TWIN ferrule 2 x 10 mm²)
Residual current IPE <= 1 µA
Nominal discharge cu...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VAL-SEC-T2-3S-350 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.