INDUSTRIAL COMPONENT DATA

SACC-DSI-FSD-4CON-L180/SH RD 1457966 PHOENIX CONTACT Flush-type connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-DSI-FSD-4CON-L180/SH RD



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-DSI-FSD-4CON-L180/SH RD
Catalog number	1457966
Category	Circular connector, mounting (PCB)
Minimum order	20 Pcs
Document ID	EO-6AB689A967
Generated	2026-11-18

Product Overview

Flush-type connector
Conn. Mont. incorp. p/ sensors/actuators, 4 poles, SPEEDCON M12, cod. D, with red contact bracket, back wall mounting/screwed, c. M16 thread, w/ straight weld connection

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1457966
Packing unit 20 pc
Minimum order quantity 20 pc
Note Made to Order (non-returnable)
Catalog page Page 62 (PC-2011)
GTIN 4046356632720
Weight per Piece (excluding packing) 14.250 g
Custom tariff number 85366990
Country of origin DE (Germany)
Dimensions
Length of the solder pin 6 mm
Ambient conditions

Ambient temperature (operation) -20 °C ... 60 °C (cable, fixed installation)
Degree of protection IP67
General
Rated current at 40°C 4 A
Rated voltage 250 V
Rated surge voltage 2.5 kV
Number of positions 4
Insulation resistance >= 100 M?
Coding D - data
Status display No
Overvoltage category II
Degree of pollution 3
Connection method Solder pins
Torque 3 Nm ... 4 Nm (Installation-side)
Mounting type Rear mounting Pg9 With flat nut
Material
Flammability rating according to UL 94 V0
Contact material CuZn
Contact surface material Au
Contact carrier material PA 6.6
Material, knurls Zinc die-cast, nickel-plated
Sealing material NBR
Standards and Regulations
Flammability rating according to UL 94 V0
Environmental Product Compliance
REACh SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 4.027250313eCl@ss 4.127250313eCl@ss 5.027143423eCl@ss 5.127143400eCl@ss 6.027279200eCl@ss 7.027440103eCl@ss 8.027440103eCl@ss 9.027440102
ETIM 4.0EC002061ETIM 5.0EC002061ETIM 6.0EC002061
UNSPSC 6.0131261501UNSPSC 7.0901312615...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-DSI-FSD-4CON-L180/SH RD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.