INDUSTRIAL COMPONENT DATA

SACC-DSI-MS-17CON-M12/0,5 SCO 1437135 PHOENIX CONTACT Panel feed-through

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-DSI-MS-17CON-M12/0,5 SCO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-DSI-MS-17CON-M12/0,5 SCO
Catalog number	1437135
Category	Circular connector, mounting (with cable)
Minimum order	1 Pcs
Document ID	EO-18946E3956
Generated	2026-11-18

Product Overview

Panel feed-through
Conect. plug. to be apar. wall poster., Universal, 17-pole, Male connector, straight, M12-SPEEDCON, coding: A, to free cable end, Rear mounting, M12 x 1, Single stranded wires, cable length: 0.5 m, 0.14 mm², TPE braided wire, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) item code: 1239648
Device connector rear mounting, Universal, 17-position, Pin, straight, M12-SPEEDCON, coding: A, on free cable end, Rear mounting, M12 x 1, Individual wires, cable length: 0.5 m, 0.14 mm2, TPE litz wire, Alternative product in accordance with RoHS II without Exemption 6c (Pb

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Technical dataNotesNotes on operation The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.
Order information: Lock nut is included in the scope of delivery
General Contact connection method: Crimp connection
MountingMounting type Rear mounting M12 x 1 With flat nut
Assembly note With flat nut
Product propertiesProduct type Circular connectors (device side)

Sensor type Universal
Number of positions 17
No. of cable outlets 1
Shielded no
Coding A
Thread type M12
Data management status
Article revision 08
Insulation characteristics
Overvoltage category II
Degree of pollution 3
Material specificationsFlammability rating according to UL 94 V0
Seal material NBR
Contact material CuZn
Contact surface material Au
Contact carrier material PA 6.6
Material for screw connection Zinc die-cast, nickel-plated
Electrical propertiesRated surge voltage 0.8 kV
Contact resistance <= 3 m?
Insulation resistance >= 100 M?
Nominal voltage UN 30 V (AC)
30 V (DC)
Nominal current IN 1.5 A
Max. conductor resistance 57.6 m?/m
Connection dataConductor connection
Connection method Individual wires
Contact connection type Pin
Conductor cross section 0.14 mm²
Tightening torque 1.5 Nm ... 2 Nm (Installation-side)
Mechanical propert...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-DSI-MS-17CON-M12/0,5 SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.