INDUSTRIAL COMPONENT DATA

SACCBP-M12MS-5CON-M16/5,0-920 1534452 PHOENIX CONTACT Bus system flat-type plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACCBP-M12MS-5CON-M16/5,0-920



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACCBP-M12MS-5CON-M16/5,0-920
Catalog number	1534452
Category	Circular connector, mounting (with cable)
Minimum order	1 Pcs
Document ID	EO-F17E0E0804
Generated	2026-11-18

Product Overview

Bus system flat-type plug
Conect. plug. to be apar. poster wall, CANopen®, DeviceNet™, 5-pole, halogen-free PUR, lilac red RAL 4001, shielded, Male, straight, M12-SPEEDCON, encoding: A, to free cable end, Rear mounting, M16 x 1.5, Cable connection, cable length: 5 m, CANopen®/DeviceNet™, PUR, violet, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) item code: 1239934
Rear device connector, CANopen®, DeviceNet™, 5-pin, halogen-free, reddish lilac RAL 4001, shielded, Connector, straight, M12-SPEEDCON, coding: A, on free conductor end, rear mounting, M16 x 1.5, Cable connection, cable length: 5 m, CANopen®/DeviceNet™, PUR, purple, Alternative in accordance with RoHS II without exception 6c (Pb < 0.1 %) Item no.: 1239934

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1534452
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 427 (C-2-2017)
GTIN 4046356026628
Weight per Piece (excluding packing) 309.000 g

Custom tariff number 85444290
Country of origin DE (Germany)
Dimensions
Length of cable 5 m
Ambient conditions
Ambient temperature (operation) -25 °C ... 85 °C (Plug / socket)
Degree of protection IP67
General
Note The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.
Rated current at 40°C 4 A
Rated voltage 60 V
Rated surge voltage 1.5 kV
Number of positions 5
Insulation resistance >= 100 M?
Coding A - standard
Standards/regulations M12 connector IEC 61076-2-101
Status display No
Overvoltage category II
Degree of pollution 3
Test voltage 2500 V
Insertion/withdrawal cycles > 100
Torque 2 Nm ... 3 Nm (Installation-side)
Material
Flammability rating according to UL 94 V0
Contact material CuZn
Contact surface material Ni/Au
Contact carrier material PA 6.6
Material, knurls Nickel-plated brass
Sealing material FKM
Standards and Regulations
Standard designation M12 connector
Standards/regulations IEC 61076-2-101
Flammability rating according to UL 94 V0
Cable
Cable type CAN Bus/DeviceNet
Cable type (abbreviation) 920...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACCBP-M12MS-5CON-M16/5,0-920 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.