INDUSTRIAL COMPONENT DATA

SACCBP-MS-4CON-M16/1,0-PUR SCO 1419399 PHOENIX CONTACT Flush-type connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACCBP-MS-4CON-M16/1,0-PUR SCO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACCBP-MS-4CON-M16/1,0-PUR SCO
Catalog number	1419399
Category	Circular connector, mounting (with cable)
Minimum order	1 Pcs
Document ID	EO-A22305607E
Generated	2026-11-18

Product Overview

Flush-type connector
Conect. plug. to be apar. wall poster., Universal, 4-pole, PUR, grayish black RAL 7021, shielded, Male connector, straight, M12-SPEEDCON, coding: A, at free cable end, Rear mounting, M16 x 1.5, Cable connection, cable length: 1 m, halogen-free PUR black, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) item code: 1239252

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1419399
Packing unit 1 pc
Catalog page Page 46 (C-2-2017)
GTIN 4046356533249
Weight per Piece (excluding packing) 60.000 g
Custom tariff number 85444290
Country of origin DE (Germany)
Dimensions
Length of cable 1 m
Ambient conditions
Ambient temperature (operation) -25 °C ... 85 °C (Plug / socket)

-40 °C ... 85 °C (without mechanical actuation)
Degree of protection IP67
General
Note The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.
Rated current at 40°C 4 A
Rated voltage 250 V
Rated surge voltage 2.5 kV
Number of positions 4
Insulation resistance >= 100 M?
Coding A - standard
Standards/regulations M12 connector IEC 61076-2-101
Status display No
Overvoltage category II
Degree of pollution 3
Connection method Individual wires
Insertion/withdrawal cycles > 100
Torque 3 Nm ... 4 Nm (Installation-side)
Mounting type Rear mounting M16 x 1.5 With flat nut
Material
Flammability rating according to UL 94 V0
Contact material CuZn
Contact surface material Au
Contact carrier material PA 6.6
Material, knurls Zinc die-cast, nickel-plated
Sealing material NBR
Cable
Cable type PUR halogen-free black
Cable abbreviation Li9Y-V1-C-V1-11Y
Conductor cross section 0.34 mm²
AWG signal l...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACCBP-MS-4CON-M16/1,0-PUR SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.