INDUSTRIAL COMPONENT DATA

SACCBP-MSD-4CON-PG9/2,0-933SCO 1437821 PHOENIX CONTACT Bus system flush-type plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACCBP-MSD-4CON-PG9/2,0-933SCO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACCBP-MSD-4CON-PG9/2,0-933SCO
Catalog number	1437821
Category	Circular connector, mounting (with cable)
Minimum order	1 Pcs
Document ID	EO-A7F3DDEAA3
Generated	2026-11-18

Product Overview

Bus system flush-type plug
Built-in mounting plug for bus system, PROFINET, 4-pole, M12, shielded, D-coded, SPEEDCON, rear wall mounting/screw mounting with Pg9 thread, with 2.0 m bus cable, 2 x 2 x 0.34 mm²

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1437821
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 307 (PC-2011)
GTIN 4046356458566
Weight per Piece (excluding packing) 161.200 g
Custom tariff number 85444290
Country of origin DE (Germany)
Dimensions
Length of cable 2 m
Ambient conditions
Ambient temperature (operation) -20 °C ... 60 °C (cable, fixed installation)

Degree of protection IP67
General
Note The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.
Rated current at 40°C 4 A
Rated voltage 250 V
Rated surge voltage 2.5 kV
Number of positions 4
Insulation resistance >= 100 M?
Coding D - data
Signal type/category PROFINET CAT5 (IEC 11801:2002)
Overvoltage category II
Degree of pollution 3
Insertion/withdrawal cycles >= 100
Torque 2 Nm ... 3 Nm (Installation-side)
Material
Flammability rating according to UL 94 V0
Contact material CuZn
Contact surface material Ni/Au
Contact carrier material PA 6.6
Sealing material FKM
Standards and Regulations
Flammability rating according to UL 94 V0
Cable
Cable type PROFINET PVC stranded CAT5
Cable type (abbreviation) 93B
UL AWM style 21694
Signal type/category PROFINET CAT5 (IEC 11801), 100 Mbps
EtherCAT®CAT5 (IEC 11801), 100 Mbps
Cable structure 1x...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACCBP-MSD-4CON-PG9/2,0-933SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.