INDUSTRIAL COMPONENT DATA

REL-OR3/L- 24AC/3X21 2903694 PHOENIX CONTACT Single relay

Brand: PHOENIX CONTACT | Manufacturer Part Number: REL-OR3/L-24AC/3X21



Manufacturer	PHOENIX CONTACT
MPN / Reference	REL-OR3/L-24AC/3X21
Catalog number	2903694
Category	Switching relay
Minimum order	10 Pcs
Document ID	EO-FCD46AA5F4
Generated	2026-11-18

Product Overview

Single relay
Pluggable octal relays with power contacts, 3 switched contacts, check button, mechanical display of switching position, coil voltage: 24 V AC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Relays

Additional Product Information

Key Commercial Data
Orderkey 2903694
Packing unit 10 pc
Minimum order quantity 10 pc
Catalog page Page 322 (C-5-2017)
GTIN 4046356759076
Weight per Piece (excluding packing) 89.350 g
Custom tariff number 85364190
Country of origin PL (Poland)
Dimensions
Width 35 mm
Height 35 mm
Depth 54.4 mm

Ambient conditions
Ambient temperature (operation) -40 °C ... 55 °C
Ambient temperature (storage/transport) -40 °C ... 85 °C
Coil side
Nominal input voltage UN 24 V AC
Mains frequency 50/60 Hz
Typical input current at UN 108 mA
Typical response time 5 ms ... 15 ms (depending on phase relation)
Typical release time range 5 ms ... 20 ms (depending on phase relation)
Status display Yellow LED
Coil resistance 75 ? ±15 %
Power dissipation for nominal condition 2.59 W
Contact side
Contact type 3 PDTs
Type of switch contact Single contact
Contact material AgNi
Maximum switching voltage 250 V DC
440 V AC
Minimum switching voltage 10 V (At 24 mA)
Min. switching current 10 mA (at 24 V)
Maximum inrush current 30 A (20 ms, N/O contact)
Limiting continuous current 10 A
Interrupting rating (ohmic load) max. 240 W (at 24 V DC)
124 W (at 48 V DC)
108 W (at 60 V DC)
52 W (at 110 V DC)
48 W (at 220 V DC)
2500 VA (for 250 V AC)
Motor load according to UL 508 1/2 HP, 240 V AC (N/O contact)
General
Note The outputs are not suitable for switching different outer conductors.
Do not use to separate SELV / PELV circuits from other circuits, because safe isolation is not guaranteed.
Test voltage relay winding/rel...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / REL-OR3/L-24AC/3X21 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.