INDUSTRIAL COMPONENT DATA

# PML-T102 (26X280)R CUS 1014251 PHOENIX CONTACT Pipeline markers

**Brand: PHOENIX CONTACT | Manufacturer Part Number: PML-T102 (26X280)R CUS**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | PML-T102 (26X280)R CUS |
| Catalog number | 1014251 |
| Category | Warning/signing plate |
| Minimum order | 1 Pcs |
| Document ID | EO-A67708B528 |
| Generated | 2026-11-19 |

## Product Overview

Pipeline markers
Pipe marker, available: by lines, red, labelled according to customer specifications: Steam, mounting class: glued, diameter: 0 mm, usable area: 26 x 280 mm

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > CABINET add-on |

## Additional Product Information

Key Commercial Data
Orderkey 1014251
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 343 (C-5-2013)
GTIN 4046356784474
Weight per Piece (excluding packing) 1.990 g
Custom tariff number 49119900
Country of origin DE (Germany)
Dimensions
Length (b) 26 mm
Width (a) 280 mm
Height (c) 26 mm

Diameter 0.00 mm
Ambient conditions
Ambient temperature (operation) -40 °C ... 150 °C
Recommended storage conditions 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.
General
Color red
Type Rectangle
Components Silicone-free
Material Polyester
RoHS compliant Yes
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Printing Steam
Number of individual labels per row 3
Adhesive Acrylic
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Procedure
Test duration 96 h
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Procedure A
Test duration 96 h
Salt spray testing result Test passed
Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07
Result Test passed
Foil strength 50 µm
Adhesive strength 46 µm
Marking mounting type adhesive
Standards and Regulations
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Classifications
eCl@ss 10.0.140200202eCl@ss 4.027141199eCl@ss 4.127141199eCl@ss 5.027371301eCl@ss 5.127371300eCl@ss 6.040200100eCl@ss....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PML-T102 (26X280)R CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.