INDUSTRIAL COMPONENT DATA

PML-T107 (52X560)R CUS 1014262 PHOENIX CONTACT Pipeline markers

Brand: PHOENIX CONTACT | Manufacturer Part Number: PML-T107 (52X560)R CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	PML-T107 (52X560)R CUS
Catalog number	1014262
Category	Warning/signing plate
Minimum order	1 Pcs
Document ID	EO-8CFEF11081
Generated	2026-11-19

Product Overview

Pipeline markers
Pipe marker, available: by lines, purple, labelled according to customer specifications: Alkalis, mounting class: glued, diameter: 0 mm, usable area: 52 x 560 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on

Additional Product Information

Key Commercial Data
Orderkey 1014262
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 345 (C-5-2013)
GTIN 4046356784689
Weight per Piece (excluding packing) 1.990 g
Custom tariff number 49119900
Country of origin DE (Germany)
Dimensions
Length (b) 52 mm
Width (a) 560 mm
Height (c) 52 mm

Diameter 0.00 mm
Ambient conditions
Ambient temperature (operation) -40 °C ... 150 °C
Recommended storage conditions 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.
General
Color violet
Type Rectangle
Components Silicone-free
Material Polyester
RoHS compliant Yes
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Printing Alkalis
Number of individual labels per row 1
Adhesive Acrylic
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Procedure
Test duration 96 h
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Procedure A
Test duration 96 h
Salt spray testing result Test passed
Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07
Result Test passed
Foil strength 50 µm
Adhesive strength 46 µm
Marking mounting type adhesive
Standards and Regulations
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Classifications
eCl@ss 10.0.140200202eCl@ss 4.027141199eCl@ss 4.127141199eCl@ss 5.027371301eCl@ss 5.127371300eCl@ss 6.040200100eC...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PML-T107 (52X560)R CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.