INDUSTRIAL COMPONENT DATA

# VC-MP-T2-R-M25 1886647 PHOENIX CONTACT Housing

**Brand: PHOENIX CONTACT | Manufacturer Part Number: VC-MP-T2-R-M25**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | VC-MP-T2-R-M25 |
| Catalog number | 1886647 |
| Category | Housing for rectangular connectors |
| Minimum order | 5 Pcs |
| Document ID | EO-FFAEFBFD1C |
| Generated | 2026-11-18 |

## Product Overview

Housing
Aerial housing, Article family: VARIOCON, construction: VC2, housing material: Zinc injected casting, color: gray. In the use of fibre optic conductors, the bending radii of the cable manufacturer must be considered.

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Field Device Connectors (FDC) |

## Additional Product Information

Key Commercial Data
Orderkey 1886647
Packing unit 5 pc
Catalog page Page 367 (PC-2009)
GTIN 4017918848064
Weight per Piece (excluding packing) 255.930 g
Custom tariff number 85389099
Country of origin PL (Poland)
Dimensions
Height 65 mm
Width 33 mm
Length 74 m
Ambient conditions
Ambient temperature (operation) -40 °C ... 125 °C

General
Note When using fiber optics, the bending radii of the cable manufacturers must be observed.
Size VC2
Housing type Sleeve housing
Locking type Screw locking, knurled head
Tightening torque, mounting screw 1.5 Nm ±0.3 Nm
No. of cable outlets 1
Cable outlet Angled
Type of the screw connection M25
Housing material Zinc die-cast
Seal material EPDM
Material of locking screw Nickel-plated brass
Flammability rating according to UL 94 V0
Standards and Regulations
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 4.027140816eCl@ss 4.127140816eCl@ss 5.027371205eCl@ss 5.127261200eCl@ss 6.027261200eCl@ss 7.027440202eCl@ss 8.027440202eCl@ss 9.027440202
ETIM 2.0EC000437ETIM 3.0EC000437ETIM 4.0EC000437ETIM 5.0EC000437ETIM 6.0EC000437
UNSPSC 6.0131261502UNSPSC 7.090131261502UNSPSC 1131261502UNSPSC 12.0131261502UNSPSC 13.231261501

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VC-MP-T2-R-M25 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.