INDUSTRIAL COMPONENT DATA

SAC-4P-M12MRT/10,0-PUR/M12FRT 1415199 PHOENIX CONTACT Power cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-M12MRT/10,0-PUR/M12FRT



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-M12MRT/10,0-PUR/M12FRT
Catalog number	1415199
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-E98C4C7F86
Generated	2026-11-19

Product Overview

Power cable
Power cable, 4-pole halogen-free, Cranked connector M12, coding: T, to Elbowed Female M12, coding: T, cable length: 10 m, for direct current up to 12 A/63 V
Power cable, 4-position, PUR halogen-free, black-gray RAL 7021, Plug angled M12, coding: T, on Socket angled M12, coding: T, cable length: 10 m, For direct current up to 12 A/63 V

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical dataProduct propertiesProduct type Power cable
Application Power supply
Number of positions 4
No. of cable outlets 1
Shielded no
Coding T
Data management status
Article revision 08
Insulation characteristics
Overvoltage category III
Degree of pollution 3

Material specificationsFlammability rating according to UL 94 V0
Material of grip body PP
Contact material CuZn
Contact surface material Ni/Au
Contact carrier material PA
Material for screw connection Zinc die-cast, nickel-plated
Electrical propertiesInsulation resistance >= 100 M?
Nominal voltage UN 63 V DC
Nominal current IN 12 A
Mechanical propertiesMechanical data
Insertion/withdrawal cycles > 100
ConnectorConnection 1
Type Plug angled M12
Coding type T (Power)
Connection 2
Type Socket angled M12
Coding type T (Power)
Cable/lineCable length 10 m
PUR halogen-free black [PUR]
Dimensional drawing
Cable weight 83 kg/km
UL AWM Style 20549 / 10493 (80°C/300 V)
Number of positions 4
Shielded no
Cable type PUR halogen-free black [PUR]
Conductor cross section 4x 1.5 mm²
Wire diameter incl. insulation 2.2 mm ±0.05 mm
External cable diameter 6.75 mm ±0.2 mm
Outer sheath, material PUR
External sheath, color black-gray RAL 7021
Conductor material Bare Cu litz wires
Material wire insulation PP
Single wire, color brown, white, blue, black
Thickness, insulation >= 0.26 mm
Thickness, outer sheath approx. 0.70 mm
Overall twist 4 wires, twisted
Max. conductor resistance <= 14.1 ?/km (at 20 °C)
Insulation resistance >= 1 G?*km (at 20....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-M12MRT/10,0-PUR/M12FRT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.