INDUSTRIAL COMPONENT DATA

SAC-5P- 7,5-441/MINFR PWR 1419807 PHOENIX CONTACT Power cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P- 7,5-441/MINFR PWR



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P- 7,5-441/MINFR PWR
Catalog number	1419807
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-A66218EFB0
Generated	2026-11-18

Product Overview

Power cable

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1419807
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 277 (C-4-2015)
GTIN 4046356537551
Weight per Piece (excluding packing) 1,515.500 g
Custom tariff number 85444290
Country of origin DE (Germany)
Dimensions
Length of cable 7.5 m
Ambient conditions
Ambient temperature (operation) -40 °C ... 90 °C (Plug / socket)
Degree of protection IP65
IP67

IP68
General
Rated current at 40°C 13 A
Rated voltage 63 V DC
Rated surge voltage 4000 V
Number of positions 5
Color handle area black
Insulation resistance >= 10 M?
Coding A - standard
Status display No
Protective circuit/component unwired
Overvoltage category II
Degree of pollution 3
Structure of individual litz in acc. with VDE 0295 / smallest wire diameter VDE 0295 class 5
Insertion/withdrawal cycles 100
Material
Flammability rating according to UL 94 HB
Contact material CuZn
Contact surface material AU
Contact carrier material PA 6.6
Material of grip body TPU
Material, knurls Zinc die-cast, nickel-plated
Cable
Cable type PUR/PVC gray
Cable abbreviation 11Y-JZ
Conductor cross section 2.5 mm²
AWG signal line 14
Wire colors Black 1, black 2, black 3, black 4, green/yellow
Overall twist 5 cores, twisted
External sheath, color gray RAL 7001
External cable diameter 10.80 mm
Smallest bending radius, fixed installation 81 mm
Smallest bending radius, movable installation 162 mm
Cable weight 195 kg/km
Outer sheath, material PUR
Conductor material Bare Cu litz wires
Flame resistance in ac...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P- 7,5-441/MINFR PWR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.