INDUSTRIAL COMPONENT DATA

# VS-PPC-J-4X-1227 1405387 PHOENIX CONTACT Power distributor

**Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-PPC-J-4X-1227**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | VS-PPC-J-4X-1227 |
| Catalog number | 1405387 |
| Category | Fibre optic attenuator |
| Minimum order | 1 Pcs |
| Document ID | EO-0D2F00DC6F |
| Generated | 2026-11-18 |

## Product Overview

Power distributor
H Power distributor, 4 MSTB contact inserts, metal housing, without fixing screws

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Field Device Connectors (FDC) |

## Additional Product Information

Key Commercial Data
Orderkey 1405387
Packing unit 1 pc
Catalog page Page 369 (C-2-2017)
GTIN 4046356419918
Weight per Piece (excluding packing) 133.600 g
Custom tariff number 85444290
Country of origin DE (Germany)
Ambient conditions
Ambient temperature (operation) -40 °C ... 85 °C
Ambient temperature (assembly) -5 °C ... 55 °C
Ambient temperature (storage/transport) -40 °C ... 85 °C
General data
Note This product corresponds to the PROFINET Cabling and Interconnection Technology Guideline for PROFINET

regulations, version 2.00, order no: 2.252, Chapter 11 Connectors for 24 Volt Power Supply Cabling and Chapter 13 Application specific Cabling and Interconnection Technology (AIDA)
Rated current at 40°C 16 A
Rated voltage 24 V
Number of positions 5
Degree of pollution 2
Alternative short product description Power H distributor
Locking type Push Pull
Rated voltage (II/2) 630 V
Rated voltage (III/2) 400 V
Rated voltage 250 V
Rated surge voltage (II/2) 4 kV
Rated surge voltage (III/2) 4 kV
Rated surge voltage (III/3) 4 kV
Rated current 16 A
Rated voltage (III/3) 24 V
Contact carrier material PA
Contact surface material Gold over nickel
Housing material Zinc die-cast
Standards and Regulations
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 10.0.127440390eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.1272607...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-PPC-J-4X-1227 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.