

INDUSTRIAL COMPONENT DATA

FL SWITCH 1001T-4POE 2891064 PHOENIX CONTACT

Industrial Ethernet Switch

Brand: PHOENIX CONTACT | Manufacturer Part Number: FL SWITCH 1001T-4POE



Manufacturer	PHOENIX CONTACT
MPN / Reference	FL SWITCH 1001T-4POE
Catalog number	2891064
Category	Network switch
Minimum order	1 Pcs
Document ID	EO-B11A37EB76
Generated	2026-09-21

Product Overview

Industrial Ethernet Switch

Ethernet Switch with PoE+, in accordance with the IEEE 802.3at specification. It comprises four PoE+ ports and one standard RJ45 port, all with speeds of 10/100 MBit/s.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > I/O

Additional Product Information

Key Commercial Data

Orderkey 2891064

Packing unit 1 pc

Catalog page Page 401 (C-6-2017)

GTIN 4046356764322

Weight per Piece (excluding packing) 800.000 g

Custom tariff number 85176200

Country of origin TW (Taiwan)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Width 55 mm

Height 117 mm

Depth 78 mm

Ambient conditions

Degree of protection IP20

Ambient temperature (operation) -40 °C ... 75 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Permissible humidity (operation) 5 % ... 95 % (non-condensing)

Permissible humidity (storage/transport) 5 % ... 95 % (non-condensing)

Air pressure (operation) 86 kPa ... 108 kPa (1500 m above sea level)

Air pressure (storage/transport) 66 kPa ... 108 kPa (3500 m above sea level)

Interfaces

Interface 1 Ethernet

No. of ports 1 (RJ45 ports)

Transmission physics Ethernet RJ45

Transmission speed 10/100 Mbps

Transmission length 100 m (Between transmitter / receiver)

Signal LEDs LNK/ACT, 100, POE

Interface 3 Ethernet (PoE)

No. of ports 4 (RJ45 ports)

Connection method RJ45 socket

Transmission physics Ethernet RJ45

Transmission speed 10/100 Mbps

Transmission length 100 m (Between transmitter / receiver)

Signal LEDs LNK/ACT, 100, POE

Function

Basic functions PSE, complies with IEEE 802.3at

Additional functions Autonegotiation

Status and diagnostic indicators LEDs: US1, US2(redundant voltage supply), Alarm (alarm contact), Link/Activity and PoE per Ethernet port

Signal contact....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FL SWITCH 1001T-4POE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.