INDUSTRIAL COMPONENT DATA

VS-PSC 1,5/3-M PE 1689336 PHOENIX CONTACT Contact insert

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-PSC 1,5/3-M PE



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-PSC 1,5/3-M PE
Catalog number	1689336
Category	D-Sub connector
Minimum order	10 Pcs
Document ID	EO-E55FD649CD
Generated	2026-11-18

Product Overview

Contact insert
POWER-SUBCON base housing, shielded, for recessed side, color: Green
POWER-SUBCON base socket, for 3-pin flush-mounted side, shielded, colour: green

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1689336
Packing unit 10 pc
Minimum order quantity 10 pc
Note Made to Order (non-returnable)
Catalog page Page 215 (C-2-2013)
GTIN 4017918893187
Weight per Piece (excluding packing) 6.890 g
Custom tariff number 85366990
Country of origin PL (Poland)
Mechanical characteristics
Number of positions 3
Insertion/withdrawal cycles >= 100

Connection method Printed circuit connection
Conductor cross section 0.14 mm² ... 1.5 mm²
Connection cross section AWG 28 ... 16
Mounting type Threads
Insulation resistance 1 T?
Type 09
Size of housing 3
Type of note Notes on operation
Note Only actuate MINI COMBICON connectors when under no load condition. If for operating reasons small loads must be switched, experimental values are available upon request.
Ambient conditions
Ambient temperature (operation) -20 °C ... 80 °C
Material data
Flammability rating according to UL 94 V0
Contact carrier material PA
Contact material Copper alloy
Contact surface material Tin-plated
Height 13.7 mm
Electrical characteristics
Number of positions 3
Rated current 8 A
Overvoltage category III
Degree of pollution 3
Rated voltage (III/3) 250 V
Standards and Regulations
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 4.027140816eCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127261200eCl@ss 6.027261200eCl@ss 7.027440205eCl@ss 8.027...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-PSC 1,5/3-M PE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.